

HP ProBook 4710s Notebook PC

Maintenance and Service Guide

© Copyright 2009 Hewlett-Packard Development Company, L.P.

AMD is a registered trademark of Advanced Micro Devices, Inc.

Bluetooth is a trademark owned by its proprietor and used by Hewlett-Packard Company under license. Intel, Core, and Celeron are trademarks of Intel Corporation in the United States and other countries. Microsoft, Windows, and Windows Vista are U.S. registered trademarks of Microsoft Corporation. SD Logo is a trademark of its proprietor.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

First Edition: April 2009

Document Part Number: 536498-001

MSG revision history

Revision	Publication date	Description	
Α	October 2009	 Added information indicating support for DDR3 memory in the following location: Memory module on page 46. 	
		 Updated commodities in the following location: <u>Product description</u> on page 1. 	
		 Added newly supported memory modules to spare parts listings in the following locations: <u>Computer major components on page 16</u>, <u>Sequential</u> <u>part number listing on page 29</u>, <u>Memory module on page 46</u>. 	
		 Added newly supported processors to spare parts listings in the following locations: <u>Computer major components on page 16</u>, <u>Sequential part number</u> <u>listing on page 29</u>, <u>Processor on page 79</u>. 	
		 Added newly supported WLAN modules to spare parts listings in the following locations: <u>Computer major components on page 16</u>, <u>Sequential</u> <u>part number listing on page 29</u>, <u>WLAN module on page 56</u>. 	
		 Added newly supported hard drives to spare parts listings in the following locations: <u>Computer major components on page 16</u>, <u>Mass storage devices</u> on page 27, <u>Sequential part number listing on page 29</u>, <u>Hard drive</u> on page 53. 	
		 Added a newly supported Bluetooth module to spare parts listings in the following locations: <u>Computer major components on page 16</u>, <u>Sequential</u> part number listing on page 29, <u>Bluetooth module on page 55</u>. 	
		 Added newly supported system boards to spare parts listings in the following locations: <u>Computer major components on page 16</u>, <u>Sequential part number</u> <u>listing on page 29</u>, <u>System board on page 81</u>. 	
		 Added newly supported AC adapter to spare parts listings in the following locations: <u>Miscellaneous parts on page 28</u>, <u>Sequential part number listing on page 29</u>. 	
		 Changes to top cover descriptions in the following locations: <u>Computer major components on page 16</u>, <u>Sequential part number listing on page 29</u>, <u>Top cover on page 66</u>. 	
		 Deleted display cable spare part from the following locations: <u>Display</u> assembly components on page 24, <u>Sequential part number listing</u> on page 29, <u>Display assembly on page 60</u>. 	

Revision	Publication date	Description	
В	January 2011	Updated the WLAN modules in the following locations: Product description on page 1, Computer major components on page 16, Sequential part number listing on page 29, WLAN module on page 56.	
		 Updated the hard drives in the following locations: <u>Product description</u> on page 1, <u>Computer major components on page 16</u>, <u>Sequential part</u> number listing on page 29, <u>Hard drive on page 53</u>. 	
		 Updated the AC adapters in the following locations: <u>Miscellaneous parts</u> on page 28, <u>Sequential part number listing on page 29</u>. 	
		 Updated the processors in the following locations: <u>Product description</u> on page 1, <u>Computer major components on page 16</u>, <u>Sequential part</u> number listing on page 29, <u>Processor on page 79</u>. 	
		 Added the Hard Drive Hardware Kit in the following locations: <u>Mass storage</u> devices on page 27, <u>Miscellaneous parts on page 28</u>, <u>Sequential part number listing on page 29</u>, <u>Hard drive on page 53</u>. 	
		 Added the Battery Latch Kit in the following locations: Miscellaneous parts on page 28, Sequential part number listing on page 29. 	
		Updated the memory modules in the following locations: Computer major components on page 16, Sequential part number listing on page 29, Memory module on page 46.	

Safety warning notice

⚠ WARNING! To reduce the possibility of heat-related injuries or of overheating the computer, do not place the computer directly on your lap or obstruct the computer air vents. Use the computer only on a hard, flat surface. Do not allow another hard surface, such as an adjoining optional printer, or a soft surface, such as pillows or rugs or clothing, to block airflow. Also, do not allow the AC adapter to contact the skin or a soft surface, such as pillows or rugs or clothing, during operation. The computer and the AC adapter comply with the user-accessible surface temperature limits defined by the International Standard for Safety of Information Technology Equipment (IEC 60950).

Table of contents

1	Product description	1
2	External component identification	6
	Top components	6
	Display components	6
	TouchPad	7
	Buttons, lights, and speakers	8
	Keys	9
	Front components	11
	Right-side components	12
	Left-side components	13
	Bottom components	14
3	Illustrated parts catalog	15
	Service tag	
	Computer major components	
	Display assembly components	
	Plastics Kit	
	Cable Kit	
	Mass storage devices	
	Miscellaneous parts	
	Sequential part number listing	
4	Removal and replacement procedures	35
	Preliminary replacement requirements	
	Tools required	
	Service considerations	
	Plastic parts	
	Cables and connectors	
	Drive handling	
	Grounding guidelines	
	Electrostatic discharge damage	
	Packaging and transporting guidelines	
	r donaging and transporting galdelines	00

	workstation guidelines	
	Equipment guidelines	39
Com	ponent replacement procedures	40
	Service tag	40
	Computer feet	41
	Battery	42
	Switch cover and keyboard	43
	Memory module	46
	Optical drive	48
	Speakers	50
	Palm rest	51
	Hard drive	53
	Bluetooth module	55
	WLAN module	56
	Display assembly	60
	Top cover	66
	Power button board	68
	Modem module	69
	USB connector module	71
	RTC battery	73
	Heat sink and fan	75
	RJ-45 (network) jack	77
	Processor	79
	System board	81
5 Computer So	etup	84
	puter Setup in Windows Vista and Windows XP	
·	Starting Computer Setup	84
	Using Computer Setup	
	Navigating and selecting in Computer Setup	
	Restoring factory settings in Computer Setup	
	Computer Setup menus	
	File Menu	
	Security menu	86
	Diagnostics menu	
	System Configuration menu	
Comp	puter Setup in Linux	
·	Starting Computer Setup	
	Using Computer Setup	
	Navigating and selecting in Computer Setup	
	Restoring factory settings in Computer Setup	
	Computer Setup menus	
	File menu	

	Security menu	91
	Diagnostics menu	92
	System Configuration menu	92
6 Spe	ecifications	95
	Computer specifications	95
	17.3-inch, HD+ display specifications	96
	Hard drive specifications	97
	DVD±RW and CD-RW SuperMulti Double-Layer Combo Drive with LightScribe specifications	98
	Blu-ray ROM with LightScribe DVD±RW SuperMulti DL Drive specifications	99
	DVD-ROM Drive	100
	System DMA specifications	100
	System interrupt specifications	101
	System I/O address specifications	102
	System memory map specifications	104
7 Scr	ew listing	105
	Phillips PM2.0×3.0 screw	105
	Phillips PM2.5×4.5 screw	109
	Phillips PM3.0×4.0 screw	111
	Phillips PM2.5×3.0 screw	112
	Phillips PM2.0×2.0 broadhead screw	115
	Phillips PM2.0×3.0 broadhead screw	116
	Phillips PM2.0×4.0 screw	117
	Phillips PM2.5×9.0 screw	118
	Phillips PM2.5×10.0 captive screw	119
	Phillips PM2.5×8.0 captive screw	121
	Torx T8M2.5×6.0 screw	122
8 Bac	ckup and recovery	124
	Backup and recovery in Windows Vista	124
	Overview	
	Backing up your information	124
	Performing a recovery	
	Using the Windows recovery tools	
	Using f11	
	Using a Windows Vista operating system DVD (purchased separately)	
	Backup and recovery in Windows XP	
	Overview	
	Backing up your information	
	Performing a recovery	
	Recovering your information	
	Recovering the operating system and programs	

9 Connector pin assignments	130
Audio-in (microphone)	130
Audio-out (headphone)	130
External monitor	131
HDMI	132
RJ-11 (modem)	133
RJ-45 (network)	134
Universal Serial Bus	134
10 Power cord set requirements	
Requirements for all countries and regions	135
Requirements for specific countries and regions	136
11 Recycling	137
Battery	137
Display	137
Index	143

1 Product description

Category	Description	
Product Name	HP ProBook 4710s Notebook PC	
	 Intel® Core™2 Duo T5870, 2.0 GHz, 2-MB L2 cache, 667-MHz Front Side Bus (FSB) 	
Processors	 Intel Core2 Duo T6570, 2.1 GHz, 2-MB L2 cache, TJ 100, 800-MHz FSB 	
	Intel Core2 Duo T6670, 2.2 GHz, 2-MB L2 cache, 800-MHz FSB	
	Intel Core2 Duo P7370, 2.0 GHz, 3-MB L2 cache, 1066-MHz FSB	
	 Intel Core2 Duo P7570, 2.26 GHz, 3-MB L2 cache, 1066-MHz FSB 	
	Intel Core2 Duo P8600, 2.4 GHz, 3-MB L2 cache, 1066-MHz FSB	
	 Intel Core2 Duo P8700, 2.53 GHz, 3-MB L2 cache, 1066-MHz FSB 	
	 Intel Core2 Duo T9400, 2.53 GHz, 6-MB L2 cache, 35W, 1066-MHz FSB 	
	Intel Core2 Duo T9600, 2.8 GHz, 6-MB L2 cache, 1066-MHz FSB	
	• Intel Pentium® Dual-Core T4200 2.00 GHz, 1-MB L2 cache, 800-MHz FSB	
	• Intel Pentium Dual-Core T4300 2.16 GHz, 1-MB L2 cache, 800-MHz FSB	
	• Intel Pentium Dual-Core T4400 2.20 GHz, 1MB L2 cache, 800-MHz FSB)	
	• Intel Celeron® 585, 2.16 GHz, 2-MB L2 cache, 800-MHz FSB	
	• Intel Celeron 900, 2.20 GHz, 1-MB L2 cache, 800-MHz FSB	
	• Intel Celeron Dual-Core T1600, 1.66GHz, 1-MB L2 cache, 667-MHz FSB	
	 Intel Celeron Dual-Core T1700 1.83-GHz, 1-MB L2 cache, 667-MHz FSB 	
	Intel Celeron Dual-Core T3000 1.8 GHz, 1-MB L2 cache, 800-MHz FSB	
	Intel Celeron Dual-Core T3100 1.9 GHz, 1-MB L2 cache, 800-MHz FSB	
Chipset	Northbridge: PM45 with up to 1066-MHz FSB	
	Southbridge: Intel ICH-9M	
Graphics	AMD Discrete Graphics ATI-M92S2LP with Hypermemory support	
	512-MB DDR2-500MHz (64Mx16, Qty 4)	
Panels	All display assemblies include 2 wireless local area network (WLAN) antennas	
	17.3-inch HD+ BrightView	
	• 17.3-inch HD+	

ategory Description		
	17.3-inch HD+ BrightView with camera	
	17.3-inch HD+ with camera	
Memory	2 customer-accessible/upgradable memory module slots	
	Supports dual-channel memory	
	Supports up to 8 GB of system RAM	
	PC2-6400, 800 MHz, DDR2	
	Supports the following configurations:	
	 8192-MB total system memory (4096 × 2, dual-channel) 	
	 4096-MB total system memory (4096 × 1) 	
	 4096-MB total system memory (2048 × 2, dual-channel) 	
	 3072-MB total system memory (2048 + 1024) 	
	 2048-MB total system memory (2048 × 1) 	
	• 2048-MB total system memory (1024 × 2, dual-channel)	
	• 1024-MB total system memory (1024 × 1)	
	PC3-10600, 1333 MHz, DDR3	
	Supports the following configurations:	
	8092-MB total system memory (4096 x 2, dual-channel)	
	 4096-MB total system memory (4096 x 1) 	
	• 4096-MB total system memory (2048 x 2, dual-channel)	
	3072-MB total system memory (2048 + 1024, dual-channel)	
	• 2048-MB total system memory (2048 x 1)	
	2048-MB total system memory (1024 x 2, dual-channel)	
	1024-MB total system memory (1024 x 1)	
Hard drives Supports 9.5-mm (2.5-inch) hard drives		
	Customer-accessible	
	Serial ATA	
Supports the following drives:		
	• 500-GB, 7200-rpm	
	• 320-GB, 5400-rpm	
	• 320-GB, 7200-rpm	
	• 250-GB, 5400-rpm	
	• 250-GB, 7200-rpm	
	• 160-GB, 7200-rpm	
	HP 3D DriveGuard	

Category	Description	
Optical drives	Fixed (removal of 1 screw required)	
	Customer-accessible	
	Serial ATA	
	12.7-mm tray load	
	Supports the following drives:	
	DVD±RW and CD-RW SuperMulti Double-Layer Combo Drive with LightScribe	
	 Blu-ray ROM with LightScribe DVD±RW SuperMulti DL Drive 	
	DVD-ROM Drive	
Diskette drive	Supports external USB diskette drive only	
	Supports boot from external USB diskette drive	
Audio	HD+ audio-ADI1984AJCPZ	
	Integrated microphone	
	Stereo speakers (2)	
Modem	56K v.92 MDC 1.5-inch data/fax modem with digital line guard	
Ethernet	Marvell 10/100/1000 Ethernet network interface card (NIC)	
	S3/S4/S5 wake on LAN: AC-yes	
Wireless	Integrated WLAN options by way of wireless module:	
	2 WLAN antennas built into display assembly	
	Support for no-WLAN option	
	Support for the following WLAN formats:	
	 Broadcom 4322 802.11a/b/g/n 	
	 Broadcom 4312 802.11b/g 	
	 Intel 5100 802.11a/b/g 	
	 Intel 5100 802.11a/b/g/n 	
	 Intel Wi-Fi Link 1000, 802.11b/g 	
	Intel Wi-Fi Link 1000, 802.11b/gIntel Wi-Fi Link 1000, 802.11b/g/n	
	•	
	 Intel Wi-Fi Link 1000, 802.11b/g/n 	
	 Intel Wi-Fi Link 1000, 802.11b/g/n Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter Atheros 9285G 802.11b/g/n WiFi Adapter 	
	 Intel Wi-Fi Link 1000, 802.11b/g/n Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter Atheros 9285G 802.11b/g/n WiFi Adapter 	
	 Intel Wi-Fi Link 1000, 802.11b/g/n Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter Atheros 9285G 802.11b/g/n WiFi Adapter Integrated personal area network (PAN) options by way of Bluetooth® module: 	
	 Intel Wi-Fi Link 1000, 802.11b/g/n Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter Atheros 9285G 802.11b/g/n WiFi Adapter Integrated personal area network (PAN) options by way of Bluetooth® module: Support for no-WPAN option 	

Category	Description	
	Media Card Reader supporting Memory Stick (MS), Memory Stick Pro (MSP), MultiMediaCard (MMC), MultiMediaCard (MMC) Plus, Secure Digital (SD) Memory Card, Secure Digital High Capacity (SDHC) Memory Card, xD-Picture Card (XD), xD-Picture Card (XD) Type H, and xD-Picture Card (XD) Type M	
Ports	Audio-in (stereo microphone)	
	Audio-out (stereo headphone)	
	RJ-11 (modem)	
	RJ-45 (Ethernet, includes link and activity lights)	
	USB (4)	
	HDMI	
	VGA (Dsub 15-pin) supporting 1600 \times 1200 external resolution at 75-GHz (hot plug/unplug with auto-detect)	
	Multi-pin AC power	
Keyboard/pointing devices	17.3-inch keyboard with integrated numeric keypad	
	TouchPad only, with 2 TouchPad buttons and vertical scrolling (taps enabled as default)	
Power requirements	90-W Smart AC adapter with localized cable plug support (3-wire plug with ground pin)	
	6-cell, 47-Wh Li-ion battery	
	8-cell, 63-Wh Li-ion battery	
Security Supports Kensington security lock		
Operating system	Preinstalled:	
	Windows 7 Professional 32	
	Windows 7 Home Premium 32	
	Windows Vista® Home Basic 32	
	Windows Vista Home Premium 32	
	Windows Vista Business 32	
	Windows Vista Business 32 (with Windows® XP Pro images)	
	• FreeDOS	
	Red Flag Linux (in the People's Republic of China only)	
	SUSE Linux	
	Restore media:	

Category	Description	
	Windows 7 Home Basic 32	
	Windows 7 Home Premium 32	
	Windows 7 Professional 32	
	Windows 7 Professional 64	
	Windows Vista Home Basic 32	
	Windows Vista Home Premium 32	
	Windows Vista Business 32	
	Windows Vista Business 64	
	Windows XP Professional	
	Red Flag Linux (in the People's Republic of China only)	
	SUSE Linux	
	Windows Vista (DRDVD)	
	Windows XP Pro (DRDVD)	
	Windows Vista (Office Ready; DVD)	
	Certified: Microsoft® WHQL	
	Web Support:	
	Windows Vista Home Basic 32	
	Windows Vista Home Premium 32	
	Windows Vista Business 32	
	Windows Vista Business 64	
	Windows XP Professional	
	SUSE Linux	
Serviceability	End-user replaceable parts:	
	AC adapter	
	Battery (system)	
	Hard drive	
	Memory module	
	Optical drive	
	WLAN module	

2 External component identification

Top components


Display components



Item	Component	Function
(1)	Internal display switch	Turns off the display if the display is closed while the power is on.
(2)	WLAN antenna locations	Send and receive signals from one or more WLAN devices. NOTE: The antennas are not visible from the outside of the computer. For optimal transmission, keep the areas immediately around the antennas free from obstructions. To see wireless regulatory notices, refer to the section of the Regulatory, Safety and Environmental Notices that applies to your country or region. These notices are located in Help and Support.
(3)	Internal microphone	Records sound.

Item	Item Component Function	
(4)	Webcam light (select models only)	On: The integrated camera is in use.
(5)	Webcam (select models only)	Records audio and video and captures still photographs.

TouchPad



Item	Component	Function
(1)	TouchPad*	Moves the pointer and selects or activates items on the screen.
(2)	Left TouchPad button*	Functions like the left button on an external mouse.
(3)	TouchPad scroll zone	Scrolls up or down.
(4)	Right TouchPad button*	Functions like the right button on an external mouse.

^{*}This table describes factory settings. View or change pointing device preferences as follows:

- In Windows Vista, select Start > Control Panel > Hardware and Sound > Mouse.
- In Windows XP, select Start > Control Panel > Printers and Other Hardware > Mouse.


Buttons, lights, and speakers



Item	Component	Function	
(1)	Caps lock light	On: Caps lock is on.	
(2)	Speakers (2)	Produce sound.	
(3)	Info Center/QuickLook button	Launches Info Center or QuickLook.	
(4)	Info Center/QuickLook light	 On: The computer is on. Blinking (5 times): When the computer is on, press button to launch Info Center. When the computer is off or in Hibernation, press button to launch QuickLook. Off: The computer is off or in the Standby or Hibernation state. 	

Item	Component	Function
(5)	Power light	On: The computer is on.
		 Blinking: The computer is in the Sleep state (Windows Vista) or Standby (Windows XP).
		Off: The computer is off or in Hibernation.
(6)	Power button	 When the computer is off, press the button to turn on the computer.
		 When the computer is on, press the button to shut down the computer.
		 When the computer is in Standby, press the button briefly to exit Standby.
		 When the computer is in Hibernation, press the button briefly to exit Hibernation.
		If the computer has stopped responding and Windows shutdown procedures are ineffective, press and hold the power button for at least 5 seconds to turn off the computer.

Keys



Item	Component	Function
(1)	esc key	Displays system information when pressed in combination with the fn key.
(2)	fn key	Executes frequently used system functions when pressed in combination with a function key or the esc key.
(3)	Windows logo key	Displays the Windows Start menu.
(4)	Windows applications key	Displays a shortcut menu for items beneath the pointer.


Item	Component	Function
(5)	Integrated numeric keypad keys	Can be used like the keys on an external numeric keypad when pressed in combination with the fn and num lk keys.
(6)	Function keys	Execute frequently used system functions when pressed in combination with the fn key.

Front components




Item	Component	Function
(1)	Drive light	 Blinking turquoise. The hard drive or optical drive is being accessed.
		 Amber: HP 3D DriveGuard has temporarily parked the hard drive.
(2)	Wireless switch	Turns the wireless feature on or off, but does not establish a wireless connection.
		NOTE: A wireless network must be set up in order to establish a wireless connection.
(3)	Wireless light	 On: An integrated wireless device, such as a wireless local area network (WLAN) device, the HP Broadband Wireless Module, and/or a Bluetooth device, is on.
		Off: All wireless devices are off.
(4)	Media Card Reader	Supports the following optional digital card formats:
		Memory Stick (MS)
		Memory Stick Pro (MSP)
		MultiMediaCard (MMC)
		MultiMediaCard (MMC) Plus
		Secure Digital (SD) Memory Card
		Secure Digital High Capacity (SDHC) Memory Card
		xD-Picture Card (XD)
		xD-Picture Card (XD) Type H
		xD-Picture Card (XD) Type M
(5)	Audio-out (headphone) jack	Connects optional powered stereo speakers, headphones, ear buds, a headset, or television audio.
(6)	Audio-in (microphone) jack	Connects an optional computer headset microphone, stereo array microphone, or monaural microphone.

Right-side components




Item	Component	Function	
(1)	USB ports (2)	Connect optional USB devices.	
(2)	RJ-11 (modem) jack	Connects a modem cable.	
(3)	Optical drive (select models only)	Reads optical discs and, on select models, also writes to optical discs.	
4)	Optical drive light (select models only)	On: The optical drive is being accessed.	
(5)	Battery light	 Amber: A battery is charging. Turquoise: A battery is close to full charge capacity. Blinking amber: A battery that is the only available power source has reached a low battery level. When the battery reaches a critical battery level, the battery light begins blinking rapidly. Off: If the computer is plugged into an external power source, the light turns off when all batteries in the computer are fully charged. If the computer is not plugged into an external power source, the light stays off until the battery reaches a low battery level. 	
(6)	Power connector	Connects an AC adapter.	

Left-side components



Item	Component	Function
(1)	ExpressCard slot	Supports optional ExpressCards.
(2)	Security cable slot	Attaches an optional security cable to the computer.
		NOTE: The security cable is designed to act as a deterrent, but it may not prevent the computer from being mishandled or stolen.
(3)	RJ-45 (network) jack	Connects a network cable.
(4)	Vent	Enables airflow to cool internal components.
		NOTE: The computer fan starts up automatically to cool internal components and prevent overheating. It is normal for the internal fan to cycle on and off during routine operation.
(5)	External monitor port	Connects an external VGA monitor or projector.
(6)	HDMI port	Connects an optional HDMI device.
(7)	USB ports (2)	Connect optional USB devices.

Bottom components



Item	Component	Function
(1)	Battery release latches (2)	Release the battery from the battery bay.
(2)	Battery bay	Holds the battery.


3 Illustrated parts catalog

Service tag


The service tag, affixed to the bottom of the computer, provides information that may be needed when troubleshooting system problems. The service tag provides the following information:

- (1) Product name: This is the product name affixed to the front of the computer.
- (2) Serial number (s/n): This is an alphanumeric identifier that is unique to each product.
- (3) Part number/Product number (p/n): This number provides specific information about the product's hardware components. The part number helps a service technician to determine what components and parts are needed.
- **(4)** Model description: This is the alphanumeric identifier used to locate documents, drivers, and support for the computer.
- (5) Warranty period: Describes the duration of the warranty period for this computer.

When ordering parts or requesting information, provide the computer serial number and model description provided on the service tag.



Computer major components



Item	Description	Spare part number
(1)	Display assembly (includes 2 WLAN antenna transceivers and cables)	
	17.3-inch, HD+ BrightView display assembly with camera	535777-001
	17.3-inch, HD+ BrightView display assembly	535779-001

Item	Description	Spare part numbe
	17.3-inch, HD+ display assembly with camera	535778-001
	17.3-inch, HD+ display assembly	535776-001
	Display internal components: (not illustrated)	
	Display bezel:	
	Models equipped with a webcam	535769-001
	Models not equipped with a webcam	535770-001
	Display Cable Kit (includes wireless antenna and webcam cables)	535771-001
	Display hinges (left and right hinges)	535772-001
2)	Switch cover	535758-001
3)	Keyboard	
	For use in Arabia	535798-171
	For use in Brazil	535798-201
	For use in Bulgaria	535798-261
	For use in Czech Republic	535798-221
	For use in Denmark	535798-081
	For use in Europe	535798-B31
	For use in Europe A4	535798-A41
	For use in French Canada	535798-121
	For use in France	535798-051
	For use in Greece	535798-DJ1
	For use in Germany	535798-041
	For use in Hungary	535798-211
	For use in Iceland	535798-DD1
	For use in Israel	535798-BB1
	For use in Italy	535798-061
	For use in Japan	535798-291
	For use in South Korea	535798-AD1
	For use in Latin America	535798-161
	For use in Norway	535798-091
	For use in Portugal	535798-131
	For use in Russia	535798-251
	For use in Sweden/Finland	535798-B71
	For use in Slovakia	535798-231
	For use in Spain	535798-071

Item	Description	Spare part number			
	For use in Switzerland	535798-BG1			
	For use in Thailand	535798-281			
	For use in Turkey	535798-141			
	For use in Taiwan	535798-AB1			
	For use in United Kingdom	535798-031			
	For use in the United States	535798-001			
(4)	Palm rest (includes TouchPad)	535775-001			
(5)	RJ-45 (network) cable (included in Cable Kit, spare part number 535757-001)				
(6)	Speakers	535795-001			
(7)	Top cover	535796-001			
(8)	RJ-11 (modem) cable (included in Cable Kit, spare part number 535757-001)				
(9)	Fan	535766-001			
(10)	Heat sink (includes replacement thermal material)	535767-001			
(11)	System board (includes replacement thermal material and the ExpressCard assembly)				
	For use in computers with DDR2 memory	574508-001			
	For use in computers with DDR3 memory	583077-001			
	Processor (includes replacement thermal material) (not illustrated)				
	Intel Core2 Duo processors:				
	• T5870 (2.0 GHz, 800-MHz FSB, 2-MB L2 cache)	535835-001			
	 T6570 (2.1 GHz, 800-MHz FSB, 2-MB L2 cache, TJ 100) (not available for Japan; only available with Intel WLAN or no WLAN) 	513598-001			
	• T6670 (2.2 GHz, 800-MHz FSB, 2-MB L2 cache)	572927-001			
	• P7370 (2.0 GHz, 1066-MHz FSB, 3-MB L2 cache) (only available with Intel WLAN)	507966-001			
	 P7570 (2.26 GHz, 1066-MHz FSB, 3-MB L2 cache) 	572930-001			
	 P8600 (2.4 GHz, 1066-MHz FSB, 3-MB L2 cache) 	507961-001			
	 P8700 (2.53 GHz, 1066-MHz FSB, 3-MB L2 cache) 	507960-001			
	• T9400 (2.53 GHz, 1066-MHz FSB, 6-MB L2 cache, 35W)	507954-001			
	• T9600 (2.8 GHz, 1066-MHz FSB, 6-MB L2 cache)	507952-001			
	Intel Pentium Dual-Core processors:				
	• T4200 (2.0 GHz, 800-MHz FSB, 1-MB L2 cache)	513599-001			
	• T4300 (2.16 GHz, 800-MHz FSB, 1-MB L2 cache)	572929-001			
	• T4400 (2.20 GHz, 800-MHz FSB, 1MB L2 cache)	582496-001			
	Intel Celeron processors:				
	• 585 (2.16 GHz, 800-MHz FSB, 2-MB L2 cache)	519898-001			
	 900 (2.20 GHz, 800-MHz FSB, 1-MB L2 cache) 	534419-001			

Item	Des	scription	Spare part number
	Inte	el Celeron Dual-Core processors:	
	•	T1600 (1.66GHz, 667-MHz FSB, 1-MB L2 cache)	532324-001
	•	T1700 (1.83-GHz, 667-MHz FSB, 1-MB L2 cache)	534084-001
	•	T3000 (1.8-GHz, 800-MHz FSB, 1-MB L2 cache)	572925-001
	•	T3100 (1.9-GHz, 800-MHz FSB, 1-MB L2 cache)	572926-001
(12)	Bat	tery connector board	535754-001
(13)	Мо	dem module	
	For	use in all countries and regions except Australia and New Zealand	510100-001
	For	use only in Australia and New Zealand	510100-011
(14)	Pov	wer button board and cable	574493-001
(15)	Pov	wer connector and cable (included in Cable Kit, spare part number 535757-001)	
(16)	Op	tical disk drive connector board	535755-001
(17)	WL	AN module	
	Bro	padcom 4322 802.11a/b/g/n WLAN modules:	
	•	Broadcom 4322 802.11a/b/g/n WLAN module for use in Antigua and Barbuda, Barbados, Belize, Canada, the Cayman Islands, Guam, Puerto Rico, Trinidad and Tobago, the U.S. Virgin Islands, and the United States	504664-001
	•	Broadcom 4322 802.11a/b/g/n WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissau, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay,	504664-002
	Bro	padcom 4312 802.11b/g WLAN modules:	
	•	Broadcom 4312 802.11b/g WLAN module for use in Antigua and Barbuda, Barbados, Belize, Canada, the Cayman Islands, Guam, Puerto Rico, Trinidad and Tobago, the U.S. Virgin Islands, and the United States	504593-003

Item Description Spare part number

Broadcom 4312 802.11b/g WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissau, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe

Intel Wi-Fi Link 5100 802.11a/b/g/n WLAN modules:

- Intel Wi-Fi Link 5100 802.11a/b/g/n WLAN module for use in all countries and regions 480985-001
- Intel Wi-Fi Link 5100 802.11a/b/g WLAN module for use in Russia and the Ukraine
 482957-001

Atheros 9285G 802.11b/g/n WiFi Adapter WLAN modules:

 Atheros 9285G 802.11b/g/n WiFi Adapter WLAN module for use in Antigua and Barbuda, Barbados, Belize, Canada, the Cayman Islands, Guam, Puerto Rico, Trinidad and Tobago, the U.S. Virgin Islands, and the United States 580101-001

504593-004

Item Description Spare part number

Atheros 9285G 802.11b/g/n WiFi Adapter WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Eguatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissau, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe

580101-002

Intel Wi-Fi Link 1000, 802.11b/g/n WLAN modules:

Intel Wi-Fi Link 1000, 802.11b/g/n WLAN module for use in Andorra, Antigua and Barbuda, Argentina, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Barbados, Belgium, Bolivia, Bosnia and Herzegovina, Brazil, Brunei, Bulgaria, Canada, Cayman Islands, Chile, China, Colombia, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, the Dominican Republic, Ecuador, Egypt, El Salvador, Estonia, Finland, France, French Guiana, Guadeloupe, Guam, Georgia, Germany, Ghana, Greece, Guatemala, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Indonesia, Ireland, Israel, Italy, Ivory Coast, Jamaica, Japan, Jordan, Kenya, Kuwait, Kyrgyzstan, Latvia, Lebanon, Liechtenstein, Lithuania, Luxembourg, Malawi, Malaysia, Malta, Martinique, Mauritius, Mexico, Monaco, Montenegro, Morocco, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Nigeria, Oman, Pakistan, Panama, Paraguay, Peru, the Philippines, Poland, Portugal, Puerto Rico, Quatar, Romania, San Marino, Saudi Arabia, Senegal, Singapore, Slovakia, Slovenia, South Africa, South Korea, Spain, Sri Lanka, Sweden, Switzerland, Taiwan, Tanzania, Thailand, Trinidad and Tobago, Turkey, United Arab Emirates, the United Kingdom, the United States, Uruguay, the U.S. Virgin Islands, Venezuela, and Vietnam

572520-001

• Intel Wi-Fi Link 1000, 802.11b/g WLAN module for use in Russia and the Ukraine

585984-001

Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter WLAN modules:


Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter WLAN module for use in Antigua and Barbuda, Aruba, the Bahamas, Barbados, Belize, Canada, Guam, Guinea, Haiti, Jamaica, the Nether Antilles, Puerto Rico, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, the United States, and the U.S. Virgin Islands

582564-001

Item	Description	Spare part number	
	• Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Argentina, Armenia, Australia, Austria, Azerbaijan, Bahrain, Belarus, Belgium, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cambodia, Cameroon, Cape Verde, Cayman Islands, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea-Bissau, Guyana, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Italy, the Ivory Coast, Japan, Jordan, Kazakhstan, Kenya, Kiribati, Kuwait, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, Qatar, the Republic of Moldova, Romania, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe	582564-002	
(18)	Base enclosure (includes rubber feet)	535752-001	
	Rubber Kit (not illustrated, contains 7 computer feet and 8 display bezel screw covers)	535793-001	
(19)	USB connector and cable (included in Cable Kit, spare part number 535757-001)		
(20)	Bluetooth cable (included in Cable Kit, spare part number 535757-001)		
(21)	Bluetooth module		
	Bluetooth 2.0 module	398393-002	
	Bluetooth 2.1 module	537921-001	
(22)	RTC battery	449137-001	
(23)	Hard drive (includes hard drive bracket)		
	500-GB, 7200-rpm	634920-001	
	320-GB, 5400-rpm	622643-001	
	320-GB, 7200-rpm	603783-001	
	250-GB, 5400-rpm	535763-001	
	250-GB, 7200-rpm	538972-001	
	160-GB, 7200-rpm	577972-001	
(24)	Optical drive (includes bezel and bracket)		
	DVD±RW and CD-RW SuperMulti Double-Layer Combo Drive with LightScribe	535761-001	
	Blu-ray ROM with LightScribe DVD±RW SuperMulti DL Drive	535759-001	
	DVD-ROM Drive	535760-001	
(25)	Memory modules		

Item	Description	Spare part number
	For use in models that use DDR2 memory	
	• 1-GB (PC2-6400, 800-MHz, DDR2)	598861-001
	• 2-GB (PC2-6400, 800-MHz, DDR2)	598858-001
	For use in models that use DDR3 memory	
	• 2-GB (PC3-10600, 1333-MHz, DDR3)	598856-001
	• 1-GB (PC3-10600, 1333-MHz, DDR3)	598859-001
(26)	8-cell, 63-Wh Li-ion battery	535753-001

Display assembly components



Item	Description	Spare part number
(1)	Display bezel	
	Display bezel with webcam	535769-001
	Display bezel without a webcam	535770-001
	Display Cable Kit, includes:	535771-001
(2a)	Webcam module cable	
(2b)	Microphone cable	
(2c)	Wireless antenna transceivers and cables	
(2d)	Display panel cable	
	Display Hinge Kit, includes:	535772-001


(3a)	Display hinge bracket	
(3b)	Display left and right hinges	
(4)	Display enclosure	535768-001

Plastics Kit



Item	Description	Spare part number
	Plastics Kit:	535780-001
(1)	ExpressCard slot bezel	
(2)	Optical drive bezel	

Cable Kit



Item	Description	Spare part number
	Cable Kit	535757-001
(1)	TouchPad cable	
(2)	RJ-11 (modem) jack cable	
(3)	RJ-45 (network) jack cable	
(4)	Bluetooth cable	
(5)	USB cable	

Mass storage devices



Item	Description	Spare part number	
(1)	Optical drives (include bezel and bracket)		
	DVD±RW and CD-RW SuperMulti Double-Layer Combo Drive with LightScribe	535761-001	
	Blu-ray ROM with LightScribe DVD±RW SuperMulti DL Drive	535759-001	
	DVD-ROM Drive	535760-001	
(2)	Hard drives (include bracket)		
	500-GB, 7200-rpm	634920-001	
	320-GB, 5400-rpm	622643-001	
	320-GB, 7200-rpm	603783-001	
	250-GB, 5400-rpm	535763-001	
	250-GB, 7200-rpm	538972-001	
	160-GB, 7200-rpm	577972-001	
	Hard Drive Hardware Kit (not illustrated)	630891-001	

Miscellaneous parts

Description	Spare part number
90W Smart AC Adapter RC/V 3W	613153-001
90W Smart AC Adapter RC/V EM 3W	613160-001
Power cords:	
For use in the United States	246959-001
For use in Australia and New Zealand	246959-011
For use in Europe, the Middle East, and Africa	246959-021
For use in the United Kingdom	246959-031
For use in Italy	246959-061
For use in Denmark	246959-081
For use in Brazil	246959-201
For use in Japan	246959-291
For use in South Korea	246959-AD1
For use in Israel	246959-BB1
Screw Kit	535794-001

Screw Kit includes:

- Phillips PM2.0×3.0 screw
- Phillips PM2.0×4.0 screw
- Phillips PM2.5×3.0 screw
- Phillips PM2.5×4.5 screw
- Phillips PM2.5×5.0 screw
- Phillips PM2.5×9.0 screw
- Phillips PM2.5×10.0 captive screw
- Phillips PM2.0×2.0 broadhead screw
- Phillips PM2.0×3.0 broadhead screw
- Phillips PM3.0×4.0 screw
- Torx T8M2.5×6.0 screw

Hard Drive Hardware Kit	630891-001
Battery Latch Kit (15.6/17.3)	602064-001

Sequential part number listing

Spare part number	Description
246959-001	Power cord for use in the United States
246959-011	Power cord for use in Australia
246959-021	Power cord for use in Europe
246959-031	Power cord for use in the United Kingdom
246959-061	Power cord for use in Italy
246959-081	Power cord for use in Denmark
246959-201	Power cord for use in Brazil
246959-291	Power cord for use in Japan
246959-AD1	Power cord for use in South Korea
246959-AG1	Power cord for use in Switzerland
246959-BB1	Power cord for use in Israel
398393-002	Bluetooth 2.0 module for use in all countries and regions except Japan and Asia Pacific
449137-001	RTC battery
480985-001	Intel Wi-Fi Link 5100 802.11a/b/g/n WLAN module for use in all countries and regions
482957-001	Intel Wi-Fi Link 5100 802.11a/b/g WLAN module for use in Russia and the Ukraine
504593-003	Broadcom 4312 802.11b/g WLAN module for use in Antigua and Barbuda, Barbados, Belize, Canada, the Cayman Islands, Guam, Puerto Rico, Trinidad and Tobago, the U.S. Virgin Islands, and the United States
504593-004	Broadcom 4312 802.11b/g WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissau, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbe
504664-001	Broadcom 4322 802.11a/b/g/n WLAN module for use in Antigua and Barbuda, Barbados, Belize, Canada, the Cayman Islands, Guam, Puerto Rico, Trinidad and Tobago, the U.S. Virgin Islands, and the United States

Spare part number	Description
504664-002	Broadcom 4322 802.11a/b/g/n WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea, Bissau, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay,
507952-001	Intel Core2 Duo T9600 processor (2.8 GHz, 1066-MHz FSB, 6-MB L2 cache)
507954-001	Intel Core2 Duo T9400 processor (2.53 GHz, 1066-MHz FSB, 6-MB L2 cache, 35W)
507960-001	Intel Core2 Duo P8700 processor (2.53 GHz, 1066-MHz FSB, 3-MB L2 cache)
507961-001	Intel Core2 Duo P8600 processor (2.4 GHz, 1066-MHz FSB, 3-MB L2 cache)
507966-001	Intel Core2 Duo P7370 processor (2.0 GHz, 1066-MHz FSB, 3-MB L2 cache) (Only available with Intel WLAN)
510100-001	Modem module for use in all countries and regions except Australia and New Zealand
510100-011	Modem module for use only in Australia and New Zealand
513598-001	Intel Core2 Duo T6570 processor (2.1 GHz, 800-MHz FSB, 2-MB L2 Cache, TJ 100) (not available for Japan. Only available with Intel WLAN or no WLAN)
513599-001	Intel Pentium Dual-Core T4200 processor (2.0 GHz, 800-MHz FSB, 1-MB L2 cache)
519898-001	Intel Celeron 585 processor (2.16 GHz, 800-MHz FSB, 2-MB L2 cache)
532324-001	Intel Celeron Dual-Core T1600 processor (1.66GHz, 667-MHz FSB, 1-MB L2 cache)
534084-001	Intel Celeron Dual-Core T1700 processor (1.83-GHz, 667-MHz FSB, 1-MB L2 cache)
534419-001	Intel Celeron 900 processor (2.20 GHz, 800-MHz FSB, 1-MB L2 cache)
535752-001	Base enclosure (includes rubber feet)
535753-001	8-cell, 63-Wh Li-ion battery
535754-001	Battery connector board
535755-001	Optical disk drive connector board
535757-001	Display Cable Kit (includes microphone, wireless antenna, display panel, and webcam cables)
535758-001	Switch cover
535759-001	Blu-ray ROM with LightScribe DVD±RW SuperMulti DL Drive

Spare part number	Description
535760-001	DVD ROM Drive
535761-001	DVD±RW and CD-RW SuperMulti Double-Layer Combo Drive with LightScribe
535763-001	250-GB, 5400-rpm hard drive
535766-001	Broadcom Bluetooth module
535767-001	Heat sink (includes replacement thermal material)
535768-001	Display enclosure
535769-001	Display bezel with webcam
535770-001	Display bezel without a webcam
535771-001	Display Cable Kit
535772-001	Display hinge
535775-001	Palm rest with TouchPad
535776-001	17.3-inch, HD+ display assembly
535777-001	17.3-inch, HD+ BrightView display assembly with camera
535778-001	17.3-inch, HD+ display assembly with camera
535779-001	17.3-inch, HD+ BrightView display assembly
535780-001	Plastics Kit (includes ExpressCard slot bezel and optical drive bezel)
535793-001	Rubber Kit
535794-001	Screw Kit
535795-001	Speaker Kit
535796-001	Top cover
535797-001	Webcam module
535798-001	Keyboard for use in the United States
535798-031	Keyboard for use in the United Kingdom
535798-041	Keyboard for use in Germany
535798-051	Keyboard for use in France
535798-061	Keyboard for use in Italy
535798-071	Keyboard for use in Spain
535798-081	Keyboard for use in Denmark
535798-091	Keyboard for use in Norway
535798-121	Keyboard for use in French Canada
535798-131	Keyboard for use in Portugal
535798-141	Keyboard for use in Turkey
535798-161	Keyboard for use in Latin America
535798-171	Keyboard for use in Arabia

Spare part number	Description
535798-201	Keyboard for use in Brazil
535798-211	Keyboard for use in Hungary
535798-221	Keyboard for use in Czech Republic
535798-231	Keyboard for use in Slovakia
535798-251	Keyboard for use in Russia
535798-261	Keyboard for use in Bulgaria
535798-281	Keyboard for use in Thailand
535798-291	Keyboard for use in Japan
535798-A41	Keyboard for use in Europe A4
535798-AB1	Keyboard for use in Taiwan
535798-AD1	Keyboard for use in South Korea
535798-B31	Keyboard for use in Europe
535798-B71	Keyboard for use in Sweden/Finland
535798-BB1	Keyboard for use in Israel
535798-BG1	Keyboard for use in Swizerland
535798-DD1	Keyboard for use in Iceland
535798-DJ1	Keyboard for use in Greece
535835-001	Intel Core2 Duo T5870 processor (2.0 GHz, 800-MHz FSB, 2-MB L2 cache)
537921-001	HP Integrated Bluetooth 2.1 module for use in all countries and regions except Japan and Asia Pacific countries and regions
538972-001	250-GB, 7200-rpm hard drive
572520-001	Intel Wi-Fi Link 1000, 802.11b/g/n WLAN module for use in Andorra, Antigua and Barbuda, Argentina, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Barbados, Belgium, Bolivia, Bosnia and Herzegovina, Brazil, Brunei, Bulgaria, Canada, Cayman Islands, Chile, China, Colombia, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, the Dominican Republic, Ecuador, Egypt, El Salvador, Estonia, Finland, France, French Guiana, Guadeloupe, Guam, Georgia, Germany, Ghana, Greece, Guatemala, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Indonesia, Ireland, Israel, Italy, Ivory Coast, Jamaica, Japan, Jordan, Kenya, Kuwait, Kyrgyzstan, Latvia, Lebanon, Liechtenstein, Lithuania, Luxembourg, Malawi, Malaysia, Malta, Martinique, Mauritius, Mexico, Monaco, Montenegro, Morocco, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Nigeria, Oman, Pakistan, Panama, Paraguay, Peru, the Philippines, Poland, Portugal, Puerto Rico, Quatar, Romania, San Marino, Saudi Arabia, Senegal, Singapore, Slovakia, Slovenia, South Africa, South Korea, Spain, Sri Lanka, Sweden, Switzerland, Taiwan, Tanzania, Thailand, Trinidad and Tobago, Turkey, United Arab Emirates, the United Kingdom, the United States, Uruguay, the U.S. Virgin Islands, Venezuela, and Vietnam
572925-001	Intel Celeron Dual-Core T3100 processor (1.9-GHz, 800-MHz FSB, 1-MB L2 cache)
572926-001	Intel Celeron Dual-Core T3000 processor (1.8-GHz, 800-MHz FSB, 1-MB L2 cache)
572927-001	Intel Core2 Duo T6670 processor (2.2 GHz, 800-MHz FSB, 2-MB L2 cache)
572929-001	Intel Pentium Dual-Core T4300 processor (2.16 GHz, 800-MHz FSB, 1-MB L2 cache)
572930-001	Intel Core2 Duo P7570 processor (2.26 GHz, 1066-MHz FSB, 3-MB L2 cache)
574493-001	Power button board (includes cable)

Spare part number	Description
574508-001	System board for use in computers with DDR2 memory (includes replacement thermal material and the ExpressCard assembly)
577972-001	160-GB, 7200-rpm hard drive
580101-001	Atheros 9285G 802.11b/g/n WiFi Adapter WLAN module for use in Antigua and Barbuda, Barbados, Belize, Canada, the Cayman Islands, Guam, Puerto Rico, Trinidad and Tobago, the U.S. Virgin Islands, and the United States
580101-002	Atheros 9285G 802.11b/g/n WiFi Adapter WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissau, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom
582564-001	Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter WLAN module for use in Antigua and Barbuda, Aruba, the Bahamas, Barbados, Belize, Canada, Guam, Guinea, Haiti, Jamaica, the Nether Antilles, Puerto Rico, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, the United States, and the U.S. Virgin Islands
582564-002	Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Argentina, Armenia, Australia, Austria, Azerbaijan, Bahrain, Belarus, Belgium, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cambodia, Cameroon, Cape Verde, Cayman Islands, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea-Bissau, Guyana, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Italy, the Ivory Coast, Japan, Jordan, Kazakhstan, Kenya, Kiribati, Kuwait, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, Qatar, the Republic of Moldova, Romania, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe
583077-001	System board for use in computers with DDR3 memory (includes replacement thermal material and the ExpressCard assembly)
584296-001	Intel Pentium Dual-Core T4400 processor (2.20 GHz, 800-MHz FSB, 1MB L2 cache)

Spare part number	Description
585984-001	Intel Wi-Fi Link 1000, 802.11b/g WLAN module for use in Russia and the Ukraine
598856-001	2-GB memory module (PC3-10600, 1333-MHz, DDR3)
598858-001	2-GB memory module (PC2-6400, 800-MHz, DDR2)
598859-001	1-GB memory module (PC3-10600, 1333-MHz, DDR3)
598861-001	1-GB memory module (PC2-6400, 800-MHz, DDR2)
602064-001	Battery Latch Kit (15.6/17.3)
603783-001	320-GB, 7200-rpm hard drive
613153-001	90W Smart AC Adapter RC/V 3W
613160-001	90W Smart AC Adapter RC/V EM 3W
622643-001	320-GB, 5400-rpm hard drive
630891-001	Hard Drive Hardware Kit
634920-001	500-GB, 7200-rpm hard drive

4 Removal and replacement procedures

Preliminary replacement requirements

Tools required

You will need the following tools to complete the removal and replacement procedures:

- Flat-bladed screwdriver
- Magnetic screwdriver
- Torx T8 screwdriver
- Phillips P0 and P1 screwdrivers

Service considerations

The following sections include some of the considerations that you must keep in mind during disassembly and assembly procedures.

NOTE: As you remove each subassembly from the computer, place the subassembly (and all accompanying screws) away from the work area to prevent damage.

Plastic parts

△ CAUTION: Using excessive force during disassembly and reassembly can damage plastic parts. Use care when handling the plastic parts. Apply pressure only at the points designated in the maintenance instructions.

Cables and connectors

△ CAUTION: When servicing the computer, be sure that cables are placed in their proper locations during the reassembly process. Improper cable placement can damage the computer.

Cables must be handled with extreme care to avoid damage. Apply only the tension required to unseat or seat the cables during removal and insertion. Handle cables by the connector whenever possible. In all cases, avoid bending, twisting, or tearing cables. Be sure that cables are routed in such a way that they cannot be caught or snagged by parts being removed or replaced. Handle flex cables with extreme care; these cables tear easily.

Drive handling

△ **CAUTION:** Drives are fragile components that must be handled with care. To prevent damage to the computer, damage to a drive, or loss of information, observe these precautions:

Before removing or inserting a hard drive, shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.

Before handling a drive, be sure that you are discharged of static electricity. While handling a drive, avoid touching the connector.

Before removing a diskette drive or optical drive, be sure that a diskette or disc is not in the drive and be sure that the optical drive tray is closed.

Handle drives on surfaces covered with at least one inch of shock-proof foam.

Avoid dropping drives from any height onto any surface.

After removing a hard drive, an optical drive, or a diskette drive, place it in a static-proof bag.

Avoid exposing a hard drive to products that have magnetic fields, such as monitors or speakers.

Avoid exposing a drive to temperature extremes or liquids.

If a drive must be mailed, place the drive in a bubble pack mailer or other suitable form of protective packaging and label the package "FRAGILE."

Grounding guidelines

Electrostatic discharge damage

Electronic components are sensitive to electrostatic discharge (ESD). Circuitry design and structure determine the degree of sensitivity. Networks built into many integrated circuits provide some protection, but in many cases, ESD contains enough power to alter device parameters or melt silicon junctions.

A discharge of static electricity from a finger or other conductor can destroy static-sensitive devices or microcircuitry. Even if the spark is neither felt nor heard, damage may have occurred.

An electronic device exposed to ESD may not be affected at all and can work perfectly throughout a normal cycle. Or the device may function normally for a while, then degrade in the internal layers, reducing its life expectancy.

△ **CAUTION:** To prevent damage to the computer when you are removing or installing internal components, observe these precautions:

Keep components in their electrostatic-safe containers until you are ready to install them.

Use nonmagnetic tools.

Before touching an electronic component, discharge static electricity by using the guidelines described in this section.

Avoid touching pins, leads, and circuitry. Handle electronic components as little as possible.

If you remove a component, place it in an electrostatic-safe container.

The following table shows how humidity affects the electrostatic voltage levels generated by different activities.

△ CAUTION: A product can be degraded by as little as 700 V.

Typical electrostatic voltage levels

	Relative humidity		
Event	10%	40%	55%
Walking across carpet	35,000 V	15,000 V	7,500 V
Walking across vinyl floor	12,000 V	5,000 V	3,000 V
Motions of bench worker	6,000 V	800 V	400 V
Removing DIPS from plastic tube	2,000 V	700 V	400 V
Removing DIPS from vinyl tray	11,500 V	4,000 V	2,000 V
Removing DIPS from Styrofoam	14,500 V	5,000 V	3,500 V
Removing bubble pack from PCB	26,500 V	20,000 V	7,000 V
Packing PCBs in foam-lined box	21,000 V	11,000 V	5,000 V

Packaging and transporting guidelines

Follow these grounding guidelines when packaging and transporting equipment:

- To avoid hand contact, transport products in static-safe tubes, bags, or boxes.
- Protect ESD-sensitive parts and assemblies with conductive or approved containers or packaging.
- Keep ESD-sensitive parts in their containers until the parts arrive at static-free workstations.
- Place items on a grounded surface before removing items from their containers.
- Always be properly grounded when touching a component or assembly.
- Store reusable ESD-sensitive parts from assemblies in protective packaging or nonconductive foam.
- Use transporters and conveyors made of antistatic belts and roller bushings. Be sure that
 mechanized equipment used for moving materials is wired to ground and that proper materials
 are selected to avoid static charging. When grounding is not possible, use an ionizer to dissipate
 electric charges.

Workstation guidelines

Follow these grounding workstation guidelines:

- Cover the workstation with approved static-shielding material.
- Use a wrist strap connected to a properly grounded work surface and use properly grounded tools and equipment.
- Use conductive field service tools, such as cutters, screwdrivers, and vacuums.
- When fixtures must directly contact dissipative surfaces, use fixtures made only of static-safe materials.
- Keep the work area free of nonconductive materials, such as ordinary plastic assembly aids and Styrofoam.
- Handle ESD-sensitive components, parts, and assemblies by the case or PCM laminate. Handle these items only at static-free workstations.
- Avoid contact with pins, leads, or circuitry.
- Turn off power and input signals before inserting or removing connectors or test equipment.

Equipment guidelines

Grounding equipment must include either a wrist strap or a foot strap at a grounded workstation.

- When seated, wear a wrist strap connected to a grounded system. Wrist straps are flexible straps with a minimum of one megohm ±10% resistance in the ground cords. To provide proper ground, wear a strap snugly against the skin at all times. On grounded mats with banana-plug connectors, use alligator clips to connect a wrist strap.
- When standing, use foot straps and a grounded floor mat. Foot straps (heel, toe, or boot straps)
 can be used at standing workstations and are compatible with most types of shoes or boots. On
 conductive floors or dissipative floor mats, use foot straps on both feet with a minimum of one
 megohm resistance between the operator and ground. To be effective, the conductive strips
 must be worn in contact with the skin.

The following grounding equipment is recommended to prevent electrostatic damage:

- Antistatic tape
- Antistatic smocks, aprons, and sleeve protectors
- Conductive bins and other assembly or soldering aids
- Nonconductive foam
- Conductive tabletop workstations with ground cords of one megohm resistance
- Static-dissipative tables or floor mats with hard ties to the ground
- Field service kits
- Static awareness labels
- Material-handling packages
- Nonconductive plastic bags, tubes, or boxes
- Metal tote boxes
- Electrostatic voltage levels and protective materials

The following table lists the shielding protection provided by antistatic bags and floor mats.

Material	Use	Voltage protection level
Antistatic plastic	Bags	1,500 V
Carbon-loaded plastic	Floor mats	7,500 V
Metallized laminate	Floor mats	5,000 V

Component replacement procedures


This section provides removal and replacement procedures.

There are as many as 89 screws, in 15 different sizes, that must be removed, replaced, or loosened when servicing the computer. Make special note of each screw size and location during removal and replacement.

Service tag


The service tag, affixed to the bottom of the computer, provides information that may be needed when troubleshooting system problems. The service tag provides the following information:

- (1) Product name: This is the product name affixed to the front of the computer.
- (2) Serial number (s/n): This is an alphanumeric identifier that is unique to each product.
- (3) Part number/Product number (p/n): This number provides specific information about the product's hardware components. The part number helps a service technician to determine what components and parts are needed.
- **(4)** Model description: This is the alphanumeric identifier used to locate documents, drivers, and support for the computer.
- (5) Warranty period: Describes the duration of the warranty period for this computer.



Computer feet

The computer feet are adhesive-backed rubber pads. The feet are included in the Rubber Kit, spare part number 535793-001 . There are 7 rubber feet that attach to the base enclosure in the locations illustrated below.



Battery


Description	Spare part number
8-cell, 63-Wh Li-ion battery	535753-001

Before disassembling the computer, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.

Remove the battery:

- 1. Turn the computer upside down on a flat surface, with the battery bay toward you.
- 2. Slide the battery release latches (1) to release the battery.
- 3. Remove the battery (2) from the computer.



Install the battery by inserting it into the battery bay until you hear a click.

Switch cover and keyboard


Description			Spare part number
Switch cover			535758-001
Keyboards for use in the	following countries or regio	ns:	
Arabia	535798-171	Japan	535798-291
Brazil	535798-201	Latin America	535798-161
Bulgaria	535798-261	Norway	535798-091
Czech Republic	535798-221	Portugal	535798-131
Denmark	535798-081	Russia	535798-251
Europe	535798-B31	Slovakia	535798-231
Europe A4	535798-A41	South Korea	535798-AD1
France	535798-051	Spain	535798-071
French Canada	535798-121	Sweden/Finland	535798-B71
Germany	535798-041	Switzerland	535798-BG1
Greece	535798-DJ1	Taiwan	535798-AB1
Hungary	535798-211	Thailand	535798-281
Iceland	535798-DD1	Turkey	535798-141
Israel	535798-BB1	United Kingdom	535798-031
Italy	535798-061	The United States	535798-001

Before removing the switch cover and keyboard, follow these steps:


- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).

Remove the switch cover and keyboard:

- 1. Remove the following screws:
 - (1) Two screw covers and two Phillips PM2.5×3.0 screws
 - (2) Three Phillips PM2.0×3.0 broadhead screws
 - (3) Two Phillips PM2.0×3.0 screws




- 2. Turn the computer right-side up, with the front toward you.
- 3. Open the computer as far as possible.
- 4. Slide the switch cover back (1) and lift it straight up (2) until it disengages from the computer.




5. Remove the two PM2.5×4.5 screws that secure the keyboard to the computer.



6. Slide the keyboard back (1), and rotate it forward (2) until it rests on the base enclosure.



7. Release the zero insertion force (ZIF) connector (1) to which the keyboard cable is attached, and disconnect the keyboard cable (2) from the system board.



8. Remove the keyboard.

Reverse this procedure to install the switch cover and keyboard.

Memory module

NOTE: Older models use DDR2 memory, while newer models use DDR3 memory. You cannot use model numbers to determine the type of memory a model uses.

NOTE: When adding a second memory module, be sure it is the same type and speed as the installed memory module. DDR2 memory modules cannot be mixed with DDR3 memory modules.

Description	Spare part number
For use in models that use DDR2 memory:	
2-GB (PC2-6400, 800-MHz, DDR2)	598858-001
1-GB (PC2-6400, 800-MHz, DDR2)	598861-001
For use in models that use DDR3 memory:	
2-GB (PC3-10600, 1333-MHz, DDR3)	598856-001
1-GB (PC3-10600, 1333-MHz, DDR3)	598859-001


Before removing the memory module, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see Battery on page 42).
- Remove the switch cover and keyboard (see Switch cover and keyboard on page 43)

Remove the memory module:

- Position the computer with the front toward you.
- Spread the retaining tabs (1) on each side of the memory module slot to release the memory module. (The edge of the module opposite the slot rises away from the computer.)

- Remove the memory module (2) by pulling the module away from the slot at an angle.
- NOTE: Memory modules are designed with a notch (3) to prevent incorrect insertion into the memory module slot.



Reverse this procedure to install a memory module.

Optical drive

NOTE: All optical drive spare part kits include an optical drive bezel.


Description	Spare part number
DVD±RW and CD-RW SuperMulti Double-Layer Combo Drive with LightScribe	535761-001
Blu-ray ROM with LightScribe DVD±RW SuperMulti DL Drive	535759-001
DVD-ROM Drive	535760-001

Before removing the optical drive, follow these steps:


- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the switch cover and keyboard (see Switch cover and keyboard on page 43)

Remove the optical drive:

- 1. Position the computer with the front toward you.
- 2. Remove the slotted PM2.5×4.5 screw (1) that secures the optical drive to the computer.
- Insert a flat-bladed screwdriver or similar tool into the optical drive tab access (2) and press the tab to the left to release the optical drive from the computer.
- Remove the optical drive (3) from the computer.



- If it is necessary to replace the optical drive bracket, position the optical drive with the rear toward you.
- Remove the two Phillips PM2.0×3.0 screws (1) that secure the optical drive bracket to the optical drive.
- Remove the optical drive bracket (2).



Reverse this procedure to reassemble and install an optical drive.

Speakers


Description	Spare part number
Speaker Kit	535795-001

Before removing the speakers, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the switch cover and keyboard (see Switch cover and keyboard on page 43).

Remove the speakers:

- 1. Disconnect the speaker cable (1) from the system board and remove the speaker cable from the clips and routing channel.
- NOTE: The two speakers are connected with a single cable.
- 2. Remove the four PM2.5×3.0 screws (2) that secure the speakers to the computer.
- 3. Remove the speakers (3) from the computer.



Reverse this procedure to install the speakers.

Palm rest


Description	Spare part number
Palm rest (includes TouchPad)	535775-001

Before removing the palm rest, follow these steps:


- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>)
- 5. Remove the switch cover and keyboard (see Switch cover and keyboard on page 43)

Remove the palm rest:

- 1. Remove the three Phillips PM2.0×3.0 broadhead screws (1) from the system board.
- 2. Slide the palm rest back (2), then lift and rotate the front edge until the palm rest rests on the system board (3).



3. Release the ZIF connector (1) to which the TouchPad cable is connected, and then disconnect the TouchPad cable (2) from the system board.



4. Remove the palm rest.

Reverse this procedure to install the palm rest.

Hard drive

NOTE: All hard drive spare part kits include a hard drive bracket.

Description	Spare part number
500-GB, 7200-rpm hard drive	634920-001
320-GB, 7200-rpm hard drive	603783-001
320-GB, 5400-rpm hard drive	622643-001
250-GB, 7200-rpm hard drive	538972-001
250-GB, 5400-rpm hard drive	535763-001
160-GB, 7200-rpm hard drive	577972-001
Hard Drive Hardware Kit	630891-001


Before removing the hard drive, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the switch cover and keyboard (see Switch cover and keyboard on page 43).
- Remove the palm rest (see <u>Palm rest on page 51</u>).


Remove the hard drive:

- 1. Position the computer with the front toward you.
- Loosen the two Phillips PM2.0×4.0 screws (1) that secure the hard drive to the computer.
- Loosen the Phillips PM2.5×10.0 captive screw (2) that secures the hard drive to the computer.
- 4. Grasp the Mylar tab (3) on the hard drive and slide the hard drive to the right to disconnect it from the system board.

5. Remove the hard drive (4) from the hard drive bay.



- 6. If it is necessary to replace the hard drive bracket, remove the two Phillips PM3.0×4.0 hard drive bracket screws (1) from each side of the hard drive.
- 7. Lift the bracket (2) straight up to remove it from the hard drive.



Reverse this procedure to reassemble and install the hard drive.

Bluetooth module

NOTE: The Bluetooth module spare part kit does not include a Bluetooth module cable. The Bluetooth module cable is included in the Cable Kit, spare part number 535757-001.


Description	Spare part number
Bluetooth 2.0 module	398393-002
Bluetooth 2.1 module	537921-001

Before removing the Bluetooth module, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- **5.** Remove the following components:
 - Switch cover and keyboard (see <u>Switch cover and keyboard on page 43</u>)
 - **b.** Palm rest (see Palm rest on page 51)
 - **c.** Hard drive (see <u>Hard drive on page 53</u>)

Remove the Bluetooth module:

- 1. Disconnect the Bluetooth module cable (1) from the system board.
- 2. Remove the Bluetooth module cable (2) from the routing path.
- 3. Remove the Bluetooth module from the clip (3) that secures it to the base enclosure.



Reverse this procedure to install the Bluetooth module.

WLAN module

Description		Spare part number
Broadcom 4322 802.11a/b/g/n WLAN modules:		
•	Broadcom 4322 802.11a/b/g/n WLAN module for use in Antigua and Barbuda, Barbados, Belize, Canada, the Cayman Islands, Guam, Puerto Rico, Trinidad and Tobago, the U.S. Virgin Islands, and the United States	504664-001
Bro	Broadcom 4322 802.11a/b/g/n WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissau, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay,	504664-002
•	Broadcom 4312 802.11/b/g WLAN module for use in Antigua and Barbuda, Barbados, Belize, Canada, the Cayman Islands, Guam, Puerto Rico, Trinidad and Tobago, the U.S.	504593-003

Virgin Islands, and the United States

Description Spare part number

Broadcom 4312 802.11/b/g WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissau, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe

504593-004

Intel Wi-Fi Link 5100 802.11a/b/g WLAN modules:

Intel Wi-Fi Link 5100 802.11a/b/g/n WLAN module for use in all countries and regions
 Intel Wi-Fi Link 5100 802.11a/b/g WLAN module for use in Russia and the Ukraine
 482957-001

Atheros 9285G 802.11b/g/n WiFi Adapter WLAN modules:

 Atheros 9285G 802.11b/g/n WiFi Adapter WLAN module for use in Antigua and Barbuda, Barbados, Belize, Canada, the Cayman Islands, Guam, Puerto Rico, Trinidad and Tobago, the U.S. Virgin Islands, and the United States

580101-001

Atheros 9285G 802.11b/g/n WiFi Adapter WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Eguatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissau, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe

580101-002

Description Spare part number

Intel Wi-Fi Link 1000, 802.11b/g/n WLAN modules:

Intel Wi-Fi Link 1000, 802.11b/g/n WLAN module for use in Andorra, Antigua and Barbuda, Argentina, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Barbados, Belgium, Bolivia, Bosnia and Herzegovina, Brazil, Brunei, Bulgaria, Canada, Cayman Islands, Chile, China, Colombia, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, the Dominican Republic, Ecuador, Egypt, El Salvador, Estonia, Finland, France, French Guiana, Guadeloupe, Guam, Georgia, Germany, Ghana, Greece, Guatemala, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Indonesia, Ireland, Israel, Italy, Ivory Coast, Jamaica, Japan, Jordan, Kenya, Kuwait, Kyrgyzstan, Latvia, Lebanon, Liechtenstein, Lithuania, Luxembourg, Malawi, Malaysia, Malta, Martinique, Mauritius, Mexico, Monaco, Montenegro, Morocco, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Nigeria, Oman, Pakistan, Panama, Paraguay, Peru, the Philippines, Poland, Portugal, Puerto Rico, Quatar, Romania, San Marino, Saudi Arabia, Senegal, Singapore, Slovakia, Slovenia, South Africa, South Korea, Spain, Sri Lanka, Sweden, Switzerland, Taiwan, Tanzania, Thailand, Trinidad and Tobago, Turkey, United Arab Emirates, the United Kingdom, the United States, Uruguay, the U.S. Virgin Islands, Venezuela, and Vietnam

572520-001

Intel Wi-Fi Link 1000, 802.11b/g WLAN module for use in Russia and the Ukraine

585984-001

Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter WLAN modules:

Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter WLAN module for use in Antigua and 582564-001 Barbuda, Aruba, the Bahamas, Barbados, Belize, Canada, Guam, Guinea, Haiti, Jamaica, the Nether Antilles, Puerto Rico, St. Kitts and Nevis, St. Lucia, St. Vincent and the Grenadines, Suriname, the United States, and the U.S. Virgin Islands

Broadcom 43224AGN 802.11a/b/g/n 2x2 WiFi Adapter WLAN module for use in Afghanistan, 582564-002 Albania, Algeria, Andorra, Angola, Argentina, Armenia, Australia, Australia, Azerbaijan, Bahrain, Belarus, Belgium, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina,

Bahrain, Belarus, Belgium, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cambodia, Cameroon, Cape Verde, Cayman Islands, the Central African Republic, Chad, Chile, the People's Republic of China, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equatorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea-Bissau, Guyana, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Italy, the Ivory Coast, Japan, Jordan, Kazakhstan, Kenya, Kiribati, Kuwait, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Palau, Panama, Papua New Guinea, Paraguay, Peru, the Philippines, Poland, Portugal, Qatar, the Republic of Moldova, Romania, Rwanda, Samoa, San Marino, Sao Tome and Principe, Saudi Arabia, Senegal, Serbia, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe


Before removing the WLAN module, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.

- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the switch cover and keyboard (see Switch cover and keyboard on page 43)
- Remove the palm rest (see <u>Palm rest on page 51</u>).

Remove the WLAN module:

- △ CAUTION: To prevent an unresponsive system, replace the wireless module only with a wireless module authorized for use in the computer by the governmental agency that regulates wireless devices in your country or region. If you replace the module and then receive a warning message, remove the module to restore computer functionality, and then contact technical support through Help and Support.
 - 1. Position the computer with the front toward you.
 - Disconnect the WLAN antenna cables (1) from the terminals on the WLAN module.
 - NOTE: The black WLAN antenna cable is connected to the WLAN module "Main" terminal. The white WLAN antenna cable is connected to the WLAN module "Aux" terminal.
 - 3. Remove the two Phillips PM2.5×3.0 screws (2) that secure the WLAN module to the computer. (The edge of the module opposite the slot rises away from the computer.)
 - 4. Remove the WLAN module (3) by sliding the module away from the slot at an angle.
 - NOTE: WLAN modules are designed with a notch (4) to prevent incorrect insertion into the WLAN module slot.



Reverse this procedure to install the WLAN module.

Display assembly

NOTE: All display assembly spare part kits include 2 WLAN antenna transceivers and cables.

Description	Spare part number
17.3-inch, HD+ BrightView display assembly with camera	535777-001
17.3-inch, HD+ BrightView display assembly	535779-001
17.3-inch, HD+ display assembly with camera	535778-001
17.3-inch, HD+ display assembly	535776-001


Before removing the display assembly, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the following components:
 - a. Switch cover (see Switch cover and keyboard on page 43)
 - b. Keyboard (see Switch cover and keyboard on page 43)
 - c. Speakers (see Speakers on page 50)
 - **d.** Palm rest (see Palm rest on page 51)

Remove the display cable:


- 1. Turn the computer right-side up, with the front toward you.
- 2. Open the computer as far as possible.
- 3. Disconnect the display panel cable (1) from the system board.
- 4. Disconnect the camera and microphone module cables (2) from the system board, and then remove the cables from the routing path (3).

Remove the wireless antenna cables (4) from the clips and routing channels built into the top cover.




Remove the display assembly:


- 1. Remove the six Phillips PM2.5×4.5 screws (1) that secure the display assembly to the computer, and then lift the display assembly straight up (2) and remove it.
 - △ CAUTION: Support the display assembly when removing the following screws. Failure to support the display assembly can result in damage to the display assembly and other computer components.




2. If it is necessary to replace the display bezel or display hinges, remove the eight rubber screw covers (1) and the eight Phillips PM2.5×4.5 screws (2) that secure the display bezel to the display assembly. The rubber screw covers are available in the Rubber Kit, spare part number 535793-001.




- 3. Lift the top inside edge of the display bezel (1) to detach it from the display assembly.
- 4. Lift the left and right inside edges of the of display bezel (2) to carefully detach them from the display assembly.
- Carefully lift the bottom inside edge of the display bezel (3) to detach it from the display assembly.
- NOTE: Make note of the routing of the display cable and the wireless antenna cable.
- **6.** Carefully remove the upper hinge cover clips from the lower hinge covers on the display assembly.
- △ CAUTION: The lower hinge covers can be damaged if care is not taken when removing the upper hinge cover clips.
- 7. Remove the display bezel from the display assembly (4). The display bezel is available using spare part numbers 535770-001 (for use only with models without a webcam) and 535769-001 (for use only with models with a webcam).



- 8. If it is necessary to replace the display hinges, remove the four Phillips PM2.5×5.0 screws (1) that secure the display panel to the display enclosure.
- 9. Remove the display panel (2).




- 10. Remove the four Phillips PM2.0×3.0 screws (1) that secure each display hinge to the display panel.
 - NOTE: When removing or replacing the eight Phillips screws, be sure to remove or replace them in the same sequence as the numbering found on the display hinges (1, 2, 3, 4).
- **11.** Remove the display hinges **(2)**. The left and right display hinges are available in the Bracket Kit, spare part number 535772-001.




- **12.** If it is necessary to replace the wireless antenna cables, lift the tape **(1)** that secures the cables to the display enclosure. The wireless antenna cables are included in the Display Cable Kit, spare part number 535771-001.
- 13. Remove the wireless antennas (2).


14. Remove the wireless antenna cables **(3)** from the clips and routing channels built into the top cover.



15. If it is necessary to replace the webcam, gently pull the webcam cables (1) from the clips and routing channels (2) built into the top cover. Lift the webcam (3) to remove it. The webcam cable is included in the Display Cable Kit, spare part number 535771-001.



16. If it is necessary to replace the microphone, lift the microphone from the clip **(1)** and gently pull the microphone cable from the routing channels **(2)**. The microphone cable is included in the Display Cable Kit, spare part number 535771-001



Reverse this procedure to reassemble and install the display assembly.

Top cover

Description	Spare part number
Top cover	535796-001


Before removing the top cover, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the following components:
 - a. Switch cover and keyboard (see Switch cover and keyboard on page 43)
 - b. Memory module (see Memory module on page 46)
 - c. Optical drive (see Optical drive on page 48)
 - d. Speakers (see Speakers on page 50)
 - e. Palm rest (see Palm rest on page 51)
 - f. WLAN module (see WLAN module on page 56)
 - g. Hard drive (see Hard drive on page 53)
 - h. Display assembly (see Display assembly on page 60)


Remove the top cover:

1. Turn the computer right-side up, with the front toward you.

2. Release the ZIF connector (1) to which the power button cable is connected, and then disconnect the cable from the system board (2).



3. Remove the 22 top cover Torx T8M2.5×6.0 screws.



4. Lift the front edge of the top cover from beneath the audio jacks (1) until it disengages from the base enclosure. Then lift the top cover (2) from the base enclosure.



Reverse this procedure to install the top cover.

Power button board


Description	Spare part number
Power button board (includes cable)	574493-001

Before removing the power button board, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the following components:
 - a. Switch cover and keyboard (see Switch cover and keyboard on page 43)
 - **b.** Optical drive (see Optical drive on page 48)
 - c. Speakers (see Speakers on page 50)
 - d. Palm rest (see Palm rest on page 51)
 - e. Hard drive (see <u>Hard drive on page 53</u>)
 - **f.** Display assembly (see <u>Display assembly on page 60</u>).
 - g. Top cover (see Top cover on page 66)

Remove the power button board:

- 1. Position the top cover upside-down with the rear toward you.
- Lift the power button board straight up and off the top cover.



Reverse this procedure to install the power button board.

Modem module

Description	Spare part number
For use in all countries and regions except Australia and New Zealand	510100-001
For use only in Australia and New Zealand	510100-011


Before removing the modem module, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the following components:
 - a. Switch cover and keyboard (see Switch cover and keyboard on page 43)
 - **b.** Memory module (see Memory module on page 46)
 - **c.** Optical drive (see Optical drive on page 48)
 - **d.** Speakers (see Speakers on page 50)
 - e. Palm rest (see Palm rest on page 51)
 - **f.** WLAN module (see WLAN module on page 56)
 - **g.** Hard drive (see <u>Hard drive on page 53</u>)
 - **h.** Display assembly (see <u>Display assembly on page 60</u>)
 - i. Top cover (see <u>Top cover on page 66</u>)

Remove the modem module:

- 1. Remove the two Phillips PM2.5×3.0 screws (1) that secure the modem module to the system board.
- 2. Lift the rear edge of the modem module (2) to release it from the system board.

3. Lift the tape (3) to disconnect the modem module cable (4).



4. Remove the modem module.

Reverse this procedure to install the modem module.

USB connector module

Description	Spare part number
Cable Kit	535757-001


Before removing the USB connector module, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the following components:
 - a. Switch cover and keyboard (see Switch cover and keyboard on page 43)
 - **b.** Memory module (see Memory module on page 46)
 - **c.** Optical drive (see Optical drive on page 48)
 - d. Speakers (see Speakers on page 50)
 - e. Palm rest (see Palm rest on page 51)
 - f. WLAN module (see WLAN module on page 56)
 - g. Hard drive (see Hard drive on page 53)
 - h. Display assembly (see <u>Display assembly on page 60</u>)
 - i. Top Cover (see Top cover on page 66)

Remove the USB connector module:

- 1. Disconnect the USB cable from the system board (1).
- 2. Lift up the USB cable from the routing channels in the base enclosure (2).
- 3. Remove the short Phillips PM2.5×3.0 screw (3) and the long Phillips PM2.5×9.0 screw (4) that secure the USB connector module to the base enclosure.

4. Remove the USB connector module (5).



Reverse this procedure to install the USB connector module.

RTC battery

Description	Spare part number
RTC battery	449137-001


Before removing the RTC battery, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the following components:
 - a. Switch cover and keyboard (see Switch cover and keyboard on page 43)
 - b. Memory module (see Memory module on page 46)
 - c. Optical drive (see Optical drive on page 48)
 - d. Speakers (see Speakers on page 50)
 - e. Palm rest (see Palm rest on page 51)
 - f. WLAN module (see WLAN module on page 56)
 - **g.** Hard drive (see <u>Hard drive on page 53</u>)
 - h. Display assembly (see Display assembly on page 60)
 - i. Top cover (see <u>Top cover on page 66</u>)

Remove the RTC battery:

1. Position the base enclosure, with the front toward you.

2. Remove the RTC battery from the socket on the system board.



Reverse this procedure to install the RTC battery.

Heat sink and fan

NOTE: The heat sink spare part kit includes replacement thermal material.

Description	Spare part number
Heat sink	535767-001
Fan	535766-001001


Before removing the heat sink and fan, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the following components:
 - a. Switch cover and keyboard (see Switch cover and keyboard on page 43)
 - **b.** Memory module (see Memory module on page 46)
 - **c.** Optical drive (see Optical drive on page 48)
 - **d.** Speakers (see Speakers on page 50)
 - e. Palm rest (see Palm rest on page 51)
 - f. WLAN module (see WLAN module on page 56)
 - **g.** Hard drive (see <u>Hard drive on page 53</u>)
 - **h.** Display assembly (see <u>Display assembly on page 60</u>)
 - i. Top cover (see Top cover on page 66)


Remove the heat sink and fan:

- 1. Following the 1 through 7 sequence stamped into the heat sink and fan, loosen the seven Phillips captive screws (1).
- 2. Disconnect the fan cable (2) from the system board.

3. Lift the heat sink and fan from the system board (3).



- 4. To remove the fan, turn the heat sink upside down and remove the three Phillips PM2.0×3.0 screws (1) that secure the fan to the heat sink.
- 5. Remove the fan (2).




Reverse this procedure to install the fan.

NOTE: To properly ventilate the computer, allow at least a 7.6-cm (3-inch) clearance on the left side of the computer.

The computer uses an electric fan for ventilation. The fan is controlled by a temperature sensor and is designed to turn on automatically when high temperature conditions exist. These conditions are affected by high external temperatures, system power consumption, power management/battery conservation configurations, battery fast charging, and software requirements. Exhaust air is displaced through the ventilation grill located on the left side of the computer.

NOTE: The thermal material must be thoroughly cleaned from the surfaces of the system board (1), (2), and (3) and the heat sink components (4), (5), and (6) and must be replaced each time the heat sink is removed. Replacement thermal material is included with all heat sink, system board, cable, and processor spare part kits.



RJ-45 (network) jack

NOTE: The Cable Kit includes replacement thermal material.

Description	Spare part number
Cable Kit	535757-001


Before removing the RJ-45 (network) jack, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the following components:
 - a. Switch cover and keyboard (see Switch cover and keyboard on page 43)
 - **b.** Memory module (see Memory module on page 46)
 - **c.** Optical drive (see Optical drive on page 48)
 - **d.** Speakers (see Speakers on page 50)
 - e. Palm rest (see Palm rest on page 51)
 - **f.** WLAN module (see WLAN module on page 56)
 - **g.** Hard drive (see <u>Hard drive on page 53</u>)

- h. Display assembly (see Display assembly on page 60)
- i. Top Cover (see <u>Top cover on page 66</u>)
- j. Heat sink and fan (see <u>Heat sink and fan on page 75</u>)

Remove the RJ-45 (network) jack:

- 1. Disconnect the RJ-45 (network) cable from the system board (1) and remove the tape (2) that secures the cable to the base enclosure.
- 2. Lift the RJ-45 (network) jack (3) straight up from the retention clips to remove it.



Reverse this procedure to install the RJ-45 (network) jack.

Processor

NOTE: All processor spare part kits include replacement thermal material.

Description	Spare part number
Intel Core2 Duo processors:	
T5870 (2.0 GHz, 800-MHz FSB, 2-MB L2 cache)	535835-001
T6570 (2.1 GHz, 800-MHz FSB, 2-MB L2 cache, TJ 100) (not available for Japan. Only available with Intel WLAN or no WLAN)	513598-001
T6670 (2.2 GHz, 800-MHz FSB, 2-MB L2 cache)	572927-001
P7370 (2.0 GHz, 1066-MHz FSB, 3-MB L2 cache) (Only available with Intel WLAN)	507966-001
P7570 (2.26 GHz, 1066-MHz FSB, 3-MB L2 cache)	572930-001
P8600 (2.4 GHz, 1066-MHz FSB, 3-MB L2 cache)	507961-001
P8700 (2.53 GHz, 1066-MHz FSB, 3-MB L2 cache)	507960-001
T9400 (2.53 GHz, 1066-MHz FSB, 6-MB L2 cache, 35W)	507954-001
T9600 (2.8 GHz, 1066-MHz FSB, 6-MB L2 cache)	507952-001
Intel Pentium Dual-Core processors:	
T4200 (2.0 GHz, 800-MHz FSB, 1-MB L2 cache)	513599-001
T4300 (2.16 GHz, 800-MHz FSB, 1-MB L2 cache)	572929-001
T4400 (2.20 GHz, 800-MHz FSB, 1MB L2 cache)	584296-001
Intel Celeron processors:	
Intel Celeron 585 (2.16 GHz, 800-MHz FSB, 2-MB L2 cache)	519898-001
Intel Celeron 900 (2.20 GHz, 800-MHz FSB, 1-MB L2 cache)	534419-001
Intel Celeron Dual-Core processors:	
T1600 (1.66 GHz, 667-MHz FSB, 1-MB L2 cache)	532324-001
T1700 (1.83-GHz, 667-MHz FSB, 1-MB L2 cache)	534084-001
T3000 (1.8-GHz, 800-MHz FSB, 1-MB L2 cache)	572926-001
T3100 (1.9-GHz, 800-MHz FSB, 1-MB L2 cache)	572925-001


Before removing the processor, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.

- Remove the battery (see <u>Battery on page 42</u>).
- 5. Remove the following components:
 - **a.** Switch cover and keyboard (see Switch cover and keyboard on page 43)
 - **b.** Memory module (see Memory module on page 46)
 - **c.** Optical drive (see Optical drive on page 48)
 - d. Speakers (see Speakers on page 50)
 - e. Palm rest (see Palm rest on page 51)
 - **f.** Hard drive (see <u>Hard drive on page 53</u>)
 - g. WLAN module (see WLAN module on page 56)
 - **h.** Display assembly (see <u>Display assembly on page 60</u>)
 - i. Top cover (see Top cover on page 66)
 - j. Heat sink and fan (see Heat sink and fan on page 75)

Remove the processor:

- 1. Position the base enclosure, with the front toward you.
- 2. Use a flat-bladed screwdriver to turn the processor locking screw (1) one-half turn counterclockwise until you hear a click.
- 3. Lift the processor (2) straight up and remove it.
- NOTE: When you install the processor, the gold triangle (3) on the processor must be aligned with the triangle (4) embossed on the processor socket.



Reverse this procedure to install the processor.

System board

NOTE: All system board spare part kits include the ExpressCard assembly.

NOTE: All system board spare part kits include replacement thermal material.

Description	Spare part number
System board for use in computers with DDR2 memory (includes replacement thermal material and the ExpressCard assembly)	574508-001
System board for use in computers with DDR3 memory (includes replacement thermal material and the ExpressCard assembly)	583077-001

Before removing the system board, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 42</u>).
- **5.** Remove the following components:
 - a. Switch cover and keyboard (see Switch cover and keyboard on page 43)
 - b. Memory module (see Memory module on page 46)
 - **c.** Optical drive (see Optical drive on page 48)
 - d. Speakers (see Speakers on page 50)
 - e. Palm rest (see Palm rest on page 51)
 - **f.** Hard drive (see Hard drive on page 53)
 - g. Display assembly (see Display assembly on page 60)
 - **h.** Top cover (see <u>Top cover on page 66</u>)


When replacing the system board, be sure that the following components are removed or disconnected from the defective system board and installed on the replacement system board:

- USB connector module cable (see USB connector module on page 71)
- Bluetooth module cable (see Bluetooth module on page 55)
- WLAN module cable (see <u>WLAN module on page 56</u>)
- RTC battery (see RTC battery on page 73)
- Heat sink and fan (see Heat sink and fan on page 75)


- RJ-45 (network) cable (see RJ-45 (network) jack on page 77)
- Processor (see <u>Processor on page 79</u>)

Remove the system board:


- 1. Position the base enclosure, with the front toward you.
- 2. Lift the power connector (1) from the retention clips in the base enclosure and remove the power cable (2) from the routing clips.




- 3. Remove the battery connector board (1).
- 4. Remove the two Phillips PM2.5×3.0 screws (2) that secure the optical drive connector board to the base enclosure.
- 5. Remove the Phillips PM2.5×3.0 screw (3) that secures the system board to the base enclosure.




6. Lift the right side of the system board at an angle (1) and remove the optical drive board (2).



- 7. Flex the left side of the base enclosure (1) until the external monitor connector and the HDMI connector are clear of the openings in the base enclosure.
- 8. Lift the right side of the system board at an angle (2) and remove it (3) from the base enclosure.



9. Turn the system board upside down with the rear panel toward you to disconnect the power cable.



Reverse this procedure to install the system board.

5 Computer Setup

Computer Setup in Windows Vista and Windows XP

Starting Computer Setup

Computer Setup is a preinstalled, ROM-based utility that can be used even when the operating system is not working or will not load.

NOTE: Some of the Computer Setup menu items listed in this guide may not be supported by your computer.

NOTE: An external keyboard or mouse connected to a USB port can be used with Computer Setup only if USB legacy support is enabled.

To start Computer Setup, follow these steps:

- 1. Turn on or restart the computer, and then press esc while the "Press the ESC key for Startup Menu" message is displayed at the bottom of the screen.
- Press f10 to enter BIOS Setup.

Using Computer Setup

Navigating and selecting in Computer Setup

The information and settings in Computer Setup are accessed from the File, Security, Diagnostics, and System Configuration menus.

To navigate and select in Computer Setup, follow these steps:

- 1. Turn on or restart the computer, and then press esc while the "Press the ESC key for Startup Menu" message is displayed at the bottom of the screen.
 - To select a menu or a menu item, use the tab key and the keyboard arrow keys and then press enter, or use a pointing device to click the item.
 - To scroll up and down, click the up arrow or the down arrow in the upper-right corner of the screen, or use the up arrow key or the down arrow key.
 - To close open dialog boxes and return to the main Computer Setup screen, press esc, and then follow the on-screen instructions.

- NOTE: You can use either a pointing device (TouchPad, pointing stick, or USB mouse) or the keyboard to navigate and make selections in Computer Setup.
- 2. Press f10 to enter BIOS Setup.
- 3. Select the File, Security, Diagnostics, or System Configuration menu.

To exit Computer Setup menus, choose one of the following methods:

 To exit Computer Setup menus without saving your changes, click the Exit icon in the lower-left corner of the screen, and then follow the on-screen instructions.

- or -

Use the tab key and the arrow keys to select **File > Ignore changes and exit**, and then press enter.

- or -

To save your changes and exit Computer Setup menus, click the **Save** icon in the lower-left corner of the screen, and then follow the on-screen instructions.

- or -

Use the tab key and the arrow keys to select **File > Save changes and exit**, and then press enter.

Your changes go into effect when the computer restarts.

Restoring factory settings in Computer Setup

NOTE: Restoring defaults will not change the hard drive mode.

To return all settings in Computer Setup to the values that were set at the factory, follow these steps:

- Turn on or restart the computer, and then press esc while the "Press the ESC key for Startup Menu" message is displayed at the bottom of the screen.
- 2. Press f10 to enter BIOS Setup.
- 3. Use a pointing device or the arrow keys to select **File > Restore defaults**.
- Follow the on-screen instructions.
- 5. To save your changes and exit, click the **Save** icon in the lower-left corner of the screen, and then follow the on-screen instructions.

- or -

Use the arrow keys to select **File > Save changes and exit**, and then press enter.

Your changes go into effect when the computer restarts.

NOTE: Your password settings and security settings are not changed when you restore the factory settings.

Computer Setup menus

The menu tables in this section provide an overview of Computer Setup options.

NOTE: Some of the Computer Setup menu items listed in this chapter may not be supported by your computer.

File Menu

Select	To do this
System Information	 View identification information for the computer and the batteries in the system.
	 View specification information for the processor, cache and memory size, system ROM, video revision, and keyboard controller version.
Set System Date and Time	Set or change the date and time on the computer.
Restore defaults	Replace the configuration settings in Computer Setup with the original factory settings. (Hard drive mode, password settings, and security settings are not changed when you restore the factory settings.)
Ignore changes and exit	Cancel any changes entered during the current session. Then exit and restart the computer.
Save changes and exit	Save any changes entered during the current session. Then exit and restart the computer. Your changes go into effect when the computer restarts.

Security menu

NOTE: Some of the menu items listed in this section may not be supported by your computer.

Select	To do this
Setup BIOS Administrator Password	Set up a BIOS administrator password.
User Management (requires a BIOS administrator	Create a new BIOS user account.
password)	View a list of ProtectTools users.
Password Policy (requires an administrator password)	Revise password policy criteria.
HP SpareKey	Enable/disable HP SpareKey (disabled by default).
Always Prompt for HP SpareKey Enrollment	Enable/disable HP SpareKey enrollment (disabled by default).
Allow Reset of HP ProtectTools security keys	Enable/disable reset of HP ProtectTools security keys.
Change Password	Enter, change, or delete a BIOS administrator password.
HP SpareKey Enrollment	Enroll or reset HP SpareKey, which is a set of security questions and answers used if you forget your password.
DriveLock Passwords	 Enable/disable DriveLock on any computer hard drive (enabled by default).
	 Change a DriveLock user password or master password.
	NOTE: DriveLock settings are accessible only when you enter Computer Setup by turning on (not restarting) the computer.

Select	To do this
Automatic DriveLock	Enable/disable Automatic DriveLock support.
Disk Sanitizer	Run Disk Sanitizer to destroy all existing data on the primary hard drive or the drive in the upgrade bay.
	CAUTION: If you run Disk Sanitizer, the data on the selected drive is destroyed permanently.
System IDs	Enter a user-defined computer asset tracking number and ownership tag.

Diagnostics menu

Select	To do this
System Diagnostics Menu	System Information—Displays the following information:
	 Identification information for the computer and the batteries in the system.
	 Specification information for the processor, cache and memory size, system ROM, video revision, and keyboard controller version.
	 Start-up Test—Verifies the system components needed for starting the computer.
	 Run-In Test—Runs a comprehensive check on system memory.
	 Hard Disk Test—Runs a comprehensive self-test on any hard drive in the system.
	 Error Log—Displays a log file if any errors have occurred.

System Configuration menu

NOTE: Some of the listed System Configuration options may not be supported by your computer.

Select	To do this
Language	Change the Computer Setup language.

Select	То	do this
Boot Options	•	Set a Startup Menu delay (in seconds).
	•	Enable/disable Custom Logo (disabled by default).
	•	Enable/disable Display Diagnostic URL (enabled by default).
	•	Enable/disable CD-ROM boot (enabled by default).
	•	Enable/disable SD Card boot (enabled by default).
	•	Enable/disable floppy boot (enabled by default).
	•	Enable/disable PXE Internal NIC boot (disabled by default).
	•	Set the Express Boot Popup delay in seconds.
	•	Set the boot order.
Device Configurations	•	Enable/disable USB legacy support (enabled by default). When enabled, USB legacy support allows the following:
		 Use of a USB keyboard in Computer Setup even when a Windows® operating system is not running.
		 Startup from bootable USB devices, including a hard drive, diskette drive, or optical drive connected by a USB port to the computer.
	•	Enable/disable fan always on while connected to an AC outlet (disabled by default).
	•	Enable/disable Data Execution Prevention (select models only; disabled by default). When enabled, the processor can disable some virus code execution, which helps to improve computer security.
	•	SATA (Serial Advanced Technology Attachment) device mode. The following options are available:
		AHCI (Advanced Host Controller Interface)
		IDE (Integrated Drive Electronics)
		NOTE: Availability of the options above varies by computer model.
	•	Enable/disable HP QuickLook 2 (enabled by default).
	•	Enable/disable Virtualization Technology (select models only; disabled by default).
	•	Enable/disable Dual-Core CPU (enabled by default).
	•	Enable/Disable Unified Extensible Firmware Interface (UEFI) mode (enabled by default).

Select	To do this
Built-In Device Options	 Enable/disable the wireless button state (enabled by default).
	 Enable/disable embedded WWAN device radio (enabled by default).
	 Enable/disable embedded Bluetooth device radio (enabled by default).
	 Enable/disable the Network Interface Controller (LAN) (enabled by default).
	 Set the wake on LAN state. Options include the following:
	 Disabled
	 Boot to Network (set by default)
	 Follow Boot Order
	 Enable/disable the optical disk drive (enabled by default).
	Enable/disable the microphone.
	 Enable/disable a modem device (enabled by default).
	 Enable/disable the embedded WLAN device (enabled by default).
	 Enable/disable LAN/WLAN switching (disabled by default).
	 Enable/disable the integrated camera (select models only; enabled by default).
Port Options (all are enabled by default)	NOTE: All port options are enabled by default.
	 Enable/disable the ExpressCard slot.
	 Enable/disable the flash media reader.
	 Enable/disable the USB port.
	CAUTION: Disabling the USB port also disables MultiBay devices and ExpressCard devices on the advanced port replicator.
Set Security Level	Change, view, or hide security levels for all BIOS menu items.
Restore Security Defaults	Restore the default security settings.

Computer Setup in Linux

Starting Computer Setup

Computer Setup is a preinstalled, ROM-based utility that can be used even when the operating system is not working or will not load.

NOTE: Some of the Computer Setup menu items listed in this guide may not be supported by your computer.

NOTE: Pointing devices are not supported in Computer Setup. You must use the keyboard to navigate and make selections.

NOTE: An external keyboard connected by USB can be used with Computer Setup only if USB legacy support is enabled.

To start Computer Setup, follow these steps:

- 1. Turn on or restart the computer.
- Before your operating system opens and while the "F10=ROM Based Setup" message is displayed in the lower-left corner of the screen, press f10.

Using Computer Setup

Navigating and selecting in Computer Setup

The information and settings in Computer Setup are accessed from the File, Security, Diagnostics, and System Configuration menus.

- 1. Open Computer Setup by turning on or restarting the computer, and then pressing f10 while the "F10 = ROM Based Setup" message is displayed in the lower-left corner of the screen. Because Computer Setup is not operating system based, it does not support the TouchPad. Navigation and selection are by keystroke:
 - To choose a menu or a menu item, use the arrow keys.
 - To select an item, press enter.
 - To close open dialog boxes and return to the main Computer Setup screen, press esc.
 - To view navigation information, press f1.
 - To change the language, press f2.
- 2. Select the File, Security, Diagnostics, or System Configuration menu.
- 3. To exit Computer Setup, choose one of the following methods:
 - To exit Computer Setup without saving your preferences, use the arrow keys to select File
 Ignore Changes And Exit. Then follow the instructions on the screen.
 - To save your preferences and exit Computer Setup, use the arrow keys to select File > Save Changes And Exit. Then follow the instructions on the screen.

Your preferences go into effect when the computer restarts.

Restoring factory settings in Computer Setup

To return all settings in Computer Setup to the values that were set at the factory, follow these steps:

- Open Computer Setup by turning on or restarting the computer, and then pressing f10 while the "F10 = ROM Based Setup" message is displayed in the lower-left corner of the screen.
- Use the arrow keys to select File > Restore Defaults, and then press enter. 2.
- When the confirmation dialog box opens, press f10. 3.
- To save your preferences and exit Computer Setup, use the arrow keys to select File > Save Changes And Exit. Then follow the instructions on the screen.
- NOTE: Your password settings and security settings are not changed when you restore the factory settings.

Computer Setup menus

The menu tables in this section provide an overview of Computer Setup options.

NOTE: Some of the Computer Setup menu items listed in this chapter may not be supported by your computer.

File menu

Select	To do this
System information	View identification information for the computer.
	 View specification information for the processor, cache and memory size, and system ROM.
Restore Defaults	Replace the configuration settings in Computer Setup with the original factory settings. (Password settings and security settings are not changed when you restore the factory settings.)
Ignore Changes And Exit	Cancel any changes entered during the current session. Then exit and restart the computer.
Save Changes And Exit	Save any changes entered during the current session. Then exit and restart the computer. Your changes go into effect when the computer restarts.

Security menu

Select	To do this	
Setup Password	Enter, change, or delete a setup password.	
Power-On Password	Enter, change, or delete a power-on password.	
Password Options	Enable/disable stringent security.	
	Enable/disable stringent security.	

DriveLock Passwords	 Enable/disable DriveLock on any computer hard drive. Enter, change, or disable DriveLock on an optional
	MultiBay hard drive.
	NOTE: DriveLock settings are accessible only when you enter Computer Setup by turning on (not restarting) the computer.
System IDs	Enter a user-defined computer asset tracking number and ownership tag.
Disk Sanitizer	Run Disk Sanitizer to destroy all existing data on the primary hard drive. The following options are available:
	Fast: Runs the Disk Sanitizer erase cycle once.
	Fast: Runs the Disk Sanitizer erase cycle once.
	 Custom: Allows you to select the desired number of Disk Sanitizer erase cycles from a list.
	CAUTION: If you run Disk Sanitizer, the data on the primary hard drive is destroyed permanently.

Diagnostics menu

Select	To do this
HDD Self-Test Option	Memory Check
Memory Check	Run a comprehensive check on system memory.

System Configuration menu

NOTE: Some of the listed System Configuration options may not be supported by your computer.

Select	To do this
Language	Change the Computer Setup language.

Boot options	 Set an f9, f10, and f12 delay when starting up.
	Enable/disable CD-ROM boot.
	Enable/disable floppy boot.
	Enable/disable internal network adapter boot.
	 Enable/disable MultiBoot, which sets a boot order that can include most boot devices in the system.
	Set the Express Boot Popup delay in seconds.
	Set the boot order.
	1st boot device: USB CD-ROM
	 2nd boot device: USB floppy
	 3rd boot device: USB SuperDisk
	4th boot device: Notebook hard drive
	 5th boot device: USB hard disk
	 6th boot device: Network controller
Device Configurations	Swap the functions of the fn key and left ctrl key.
	 Enable/disable USB legacy support. When enabled, USB legacy support allows the following:
	 Use of a USB keyboard in Computer Setup even when a your operating system is not running.
	 Startup from bootable USB devices, including a hard drive, diskette drive, or optical drive connected by a USB port to the computer.
	 Enable/disable BIOS DMA data transfers.
	 Enable/disable fan always on while connected to an AC outlet.
	Enable/disable data execution prevention.
	 Enable/disable LAN power saving mode.
	Enable/disable SATA Native Mode.
	Enable/disable Dual-Core CPU.
	Enable/disable HDD translation mode.

Built-in device options	Enable/disable embedded WLAN Device Radio.
	Enable/disable embedded Bluetooth Device Radio.
	Enable/disable Network Interface Controller (NIC)
	Enable/disable LAN/WLAN Switching.
	Enable/disable Wake on LAN.
	Enable/disable the integrated camera (webcam)
Port options	Enable/disable USB port.
	Enable/disable ExpressCard slot.

Specifications 6

Computer specifications

	Metric	U.S.
Dimensions		
Depth	27.0 cm	10.6 in
Width	41.06 cm	16.17 in
Height (front to rear)	3.20 to 3.68 cm	1.23 to 1.45 in
Weight (equipped with optical drive, hard drive, and battery)	3.08 kg	6.8 lbs
Input power		
Operating voltage	18.5 V dc @ 4.74 A-90 W	
Operating current	4.74 A	
Temperature		
Operating (not writing to optical disc)	0°C to 35°C	32°F to 95°F
Operating (writing to optical disc)	5°C to 35°C	41°F to 95°F
Nonoperating	-20°C to 60°C	-4°F to 140°F
Relative humidity		
Operating	10% to 90%	
Nonoperating	5% to 95%	
Maximum altitude (unpressurized)		
Operating	-15 m to 3,048 m	-50 ft to 10,000 ft
Nonoperating	-15 m to 12,192 m	-50 ft to 40,000 ft
Shock		
Operating	125 g, 2 ms, half-sine	
Nonoperating	200 g, 2 ms, half-sine	
Random vibration		
Operating	0.75 g zero-to-peak, 10 Hz to rate	500 Hz, 0.25 oct/min sweep

	Metric	U.S.
Nonoperating	1.50 g zero-to-peak, 10 Hz to 500 Hz, 0.5 oct/min sweep rate	
NOTE: Applicable product cofety standards enecify thermal limits for plastic surfaces. The computer energies well within		

NOTE: Applicable product safety standards specify thermal limits for plastic surfaces. The computer operates well within this range of temperatures.

17.3-inch, HD+ display specifications

	Metric	U.S.	
Dimensions			
Height	38.21 cm	15.0 in	
Width	20.83 cm	8.2 in	
Diagonal	43.94 cm	17.3 in	
Active area	38.21 × 21.49 cm	15.04 × 8.46 in	
Weight (maximum)	570 g	1.26 lbs	
Number of colors	Up to 16.8 million		
Contrast ratio	500:1 (min)-BV, 300:1 (min)-AG		
Brightness	200 nits (typical)		
Pixel resolution			
LCD mode	TN		
Format	1600 × 900		
Active area	HD+		
Backlight	LED		
Total power consumption	5.3 W		
Viewing angle	SVA		

Hard drive specifications

	500-GB	320-GB*	250-GB*	160-GB*
Dimensions				
Height	9.5 mm	9.5 mm	9.5 mm	9.5 mm
Width	70 mm	70 mm	70 mm	70 mm
Weight	101 g	101 g	101 g	101 g
Interface type	SATA	SATA	SATA	SATA
Transfer rate	100 MB/sec	100 MB/sec	100 MB/sec	100 MB/sec
Security	ATA security	ATA security	ATA security	ATA security
Seek times (typical read, including setting)				
Single track	3 ms	3 ms	3 ms	3 ms
Average	13 ms	13 ms	13 ms	13 ms
Maximum	24 ms	24 ms	24 ms	24 ms
Logical blocks	976,754,000	625,122,560	488,376,120	312,560,640
Disc rotational speed	5400 rpm	5400 rpm	5400 rpm	5400 rpm
Operating temperature	5°C to 55°C (41°F to 131°F)			

^{*1} GB = 1 billion bytes when referring to hard drive storage capacity. Actual accessible capacity is less. Actual drive specifications may differ slightly.

NOTE: Certain restrictions and exclusions apply. Contact technical support for details.

DVD±RW and **CD-RW** SuperMulti Double-Layer Combo Drive with LightScribe specifications

Applicable disc	Read:	Write:
	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD-RW, DVD-RAM	CD-R, CD-RW, DVD+R, DVD +RW, DVD-R, DVD-RW, DVD- RAM, LightScribe
Access time	CD	DVD
Random	< 150 ms	< 160 ms
Cache buffer	2 MB	
Data transfer rate		
24X CD-ROM	3,600 KB/sec	
8X DVD-ROM	10,800 KB/sec	
24X CD-R	3,600 KB/sec	
16X CD-RW	2,400 KB/sec	
8X DVD+R	10,800 KB/sec	
8x-DVD+RW	10.800 KB/sec	
8X DVD-R	10,800 KB/sec	
6X DVD-RW	8,100 KB/sec	
5X DVD-RAM	6,750 KB/sec	
4X-DVD+R Dual Layer	5,400 KB/sec	
4X-DVD-R Dual Layer	5,400 KB/sec	
Transfer mode	Multiword DMA Mode	

Blu-ray ROM with LightScribe DVD±RW SuperMulti DL Drive specifications

Applicable disc	Read:	Write:		
	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RAM, BD-ROM, BD-R, BD-RE	DVD-R(9), DVD-RW, DVD-RAM, LightScribe		
Access time	CD	DVD	Blu-ray	
Random	< 110 ms	< 130 ms	230 ms	
Cache buffer	2 MB			
Data transfer rate				
24X CD-ROM	3,600 KB/sec			
8X DVD	10,800 KB/sec			
4X BD	1,800 KB/sec			
16X CD-R	1,200 KB/sec			
16X CD-RW	1,500 KB/sec			
8X DVD+R	10,800 KB/sec			
8X DVD+RW	10,800 KB/sec			
8X DVD-R	10,800 KB/sec			
8X DVD-RW	8,100 KB/sec			
4X DVD+R Dual Layer	5,400 KB/sec			
4X DVD-R Dual Layer	5,400 KB/sec			
5X DVD-RAM	6,750 KB/sec			
Transfer mode	Multiword DMA mode 2			

DVD-ROM Drive

Applicable disc	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM		
Access time	CD	DVD	
Random	< 110 ms	< 110 ms	
Cache buffer	512 KB		
Data transfer rate			
CD-ROM (24X)	3600 KB/s (150 KB/s at 1X CD rate)		
DVD (8X)	10,800 KB/s (1,352 KB/s at 1X DVD rate)		
Multiword DMA mode 2	16.6 MB/s		

System DMA specifications

Hardware DMA	System function		
DMA0	Not applicable		
DMA1*	Not applicable		
DMA2*	Not applicable		
DMA3	Not applicable		
DMA4	Direct memory access controller		
DMA5*	Available for ExpressCard		
DMA6	Not assigned		
DMA7	Not assigned		
*ExpressCard controller can use DMA 1, 2, or 5.			

System interrupt specifications

Hardware IRQ	System function
IRQ0	System timer
IRQ1	Standard 101-/102-Key or Microsoft Natural P/S2 Keyboard with HP QLB
IRQ2	Mobile Intel® 4 Series Chipset PCI Express Root Port-2A41
IRQ3	Intel® ICH9 Family PCI Express Root Port1-2940
IRQ4	Intel® ICH9 Family PCI Express Root Port2-2942
IRQ5	Intel® ICH9 Family PCI Express Root Port3-2944
IRQ6	Intel® ICH9 Family PCI Express Root Port5-2948
IRQ7	Intel® ICH9 Family PCI Express Root Port6-294A
IRQ8	ATI Mobility Radeon HD 4330
IRQ9	Intel® WiFi Link 5100 ABG
IRQ12	Synaptics PS/2 Port TouchPad
IRQ13	Numeric data processor
IRQ16	Intel® ICH9 Family USB Universal Host Controller-2937
IRQ-17	High Definition Audio Controller
IRQ-18	Intel® ICH9 Family USB Universal Host Controller-2939
IRQ-19	Intel® ICH9 Family USB Universal Host Controller-293C
IRQ-20	Intel® ICH9 Family USB Universal Host Controller-293A
IRQ-21	Intel® ICH9M-E/M SATA AHCI Controller
IRQ-22	Intel® ICH9 Family USB Universal Host Controller-2935
*Default configuration; audio possib	ole configurations are IRQ5, IRQ7, IRQ9, IRQ10, or none.
NOTE: Francis Ocade account	LIDOO IDOA IDOS IDOS IDOO IDOAS IDOAS Etherathe infrared anthe

NOTE: ExpressCards may assert IRQ3, IRQ4, IRQ5, IRQ7, IRQ9, IRQ10, IRQ11, or IRQ15. Either the infrared or the serial port may assert IRQ3 or IRQ4.

System I/O address specifications

I/O address (hex)	System function (shipping configuration)
000-01F	Direct memory access controller
000-CF7	PCI Bus
020-021	Programmable interrupt controller
024-025	Programmable interrupt controller
028-029	Programmable interrupt controller
02C-02D	Programmable interrupt controller
02E-02F	Motherboard resources
030-031	Programmable interrupt controller
034-035	Programmable interrupt controller
038-039	Programmable interrupt controller
03C-03D	Programmable interrupt controller
040-043	System timer
04E-04F	Motherboard resources
050-053	System timer
060-060	Standard 101-/102-Key or Microsoft Natural P/S2 Keyboard with HP QLB
061-061	Motherboard resources
062-062	Microsoft ACPI-Compliant Embedded Controller
063-063	Motherboard resources
064-064	Standard 101-/102-Key or Microsoft Natural P/S2 Keyboard with HP QLB
065-065	Motherboard resources
066-066	Microsoft ACPI-Compliant Embedded Controller
067-067	Motherboard resources
070-070	Motherboard resources
070-077	System CMOS/real time clock
080-080	Motherboard resources
081-091	Direct memory access controller
092–092	Motherboard resources
093-09F	Direct memory access controller
0A0-0A1	Programmable interrupt controller
0A4-0A5	Programmable interrupt controller
0A8-0A9	Programmable interrupt controller
0AC-0AD	Programmable interrupt controller
0B0-0B1	Programmable interrupt controller

I/O address (hex)	System function (shipping configuration)	
0C0-0DF	Direct memory access controller	
0F0-0F0	Numeric data processor	
200-27F	Motherboard resources	
3B0-3BB	ATI Mobility Radeon HD 4330	
3B0-3BB	Mobile Intel® 4 Series Chipset PCI Express Root Port-2A41	
3C0-3DF	ATI Mobility Radeon HD 4330	
3C0-3DF	Mobile Intel® 4 Series Chipset PCI Express Root Port-2A41	
400-47F	Motherboard resources	
4D0-4D1	Programmable interrupt controller	
500-57F	Motherboard resources	
0D00-FFFF	PCI bus	
1000-1003	Motherboard resources	
1010-101F	Motherboard resources	
2000-20FF	Marvelll Yukon 88E88072 PCI-E Gigabit Ethernet Controller	
2000-20FF	Intel® ICH9 Family PCI Express Root Port6-294A	
3000-4FFF	Intel® ICH9 Family PCI Express Root Port5-2948	
5000-6FFF	Intel® ICH9 Family PCI Express Root Port3-2944	
7000-70FF	ATI Mobility Radeon HD 4330	
7000-70FF	Mobile Intel® 4 Series Chipset PCI Express Root Port-2A41	
8000-801F	Intel® ICH9M-E/M SATA AHCI Controller	
8020-803F	Intel® ICH9 Family USB Universal Host Controller-2936	
8040-805F	Intel® ICH9 Family USB Universal Host Controller-2935	
8060-807F	Intel® ICH9 Family USB Universal Host Controller-2934	
8080-809F	Intel® ICH9 Family USB Universal Host Controller-2939	
80A0-80BF	Intel® ICH9 Family USB Universal Host Controller-2938	
80C0-80DF	Intel® ICH9 Family USB Universal Host Controller-2937	
CF8-CFB		
80E0-80E7	Intel® ICH9M-E/M SATA AHCI Controller	
80E8-80EF	Intel® ICH9M-E/M SATA AHCI Controller	
80F0-80F3	Intel® ICH9M-E/M SATA AHCI Controller	
80F4-80F7	Intel® ICH9M-E/M SATA AHCI Controller	
EF80-EF9F	Motherboard resources	
FE00-FE0F	Motherboard resources	

I/O address (hex)	System function (shipping configuration)
FE80-FE8F	Motherboard resources
FFFF—FFFF	Motherboard resources


System memory map specifications

Memory address	System function
000A0000-000BFFFF	ATI Mobility Radeon HD 4330
000A0000-000BFFFF	Mobile Intel® 4 Series Chipset PCI Express Root Port-2A41
000A0000-000BFFFF	PCI bus
C0000000-CFFFFFF	ATI Mobility Radeon HD 4330
C0000000-CFFFFFF	Mobile Intel® 4 Series Chipset PCI Express Root Port-2A41
C0000000-DFFFFFFF	PCI bus
D0000000-D00FFFF	Intel® 82801 PCI Bridge-2448
D0100000-D0103FFF	Marvelll Yukon 88E88072 PCI-E Gigabit Ethernet Controller
D0100000-D01FFFFF	Intel® ICH9 Family PCI Express Root Port6-294A
D0200000-D41FFFF	Intel® ICH9 Family PCI Express Root Port5-2948
D4200000-D81FFFFF	Intel® ICH9 Family PCI Express Root Port3-2944

7 Screw listing

This chapter provides specification and reference information for the screws and screw locks used in the computer. All screws listed in this section are available in the Screw Kit, spare part number 535794-001.


Phillips PM2.0×3.0 screw




Color	Quantity	Length	Thread	Head diameter
Silver	21	3.0 mm	2.0 mm	5.0 mm




Where used: 2 screws that secure the optical drive bracket to the optical drive




Where used: 3 screws that secure the system board to the base enclosure




Where used: 8 screws that secure the display hinges to the display panel



Where used: 3 screws that secure the fan to the heat sink




Where used: 3 screws that secure the system board to the base enclosure.



Where used: 2 screws that secure the top cover and battery connector board to the base enclosure

Phillips PM2.5×4.5 screw




Color	Quantity	Length	Thread	Head diameter
Black	21	4.5 mm	2.5 mm	5.0 mm



Where used: 4 screws that secure the display panel to the display assembly




Where used: 2 screws that secure the keyboard to the computer



Where used: 8 screws that secure the display bezel to the display enclosure




Where used: 1 screw that secures the optical drive to the computer



Where used: 6 screws that secure the display assembly to the computer.

Phillips PM3.0×4.0 screw




Color	Quantity	Length	Thread	Head diameter
Silver	4	4.0 mm	3.0 mm	5.0 mm




Where used: 4 screws that secure the hard drive bracket to the hard drive

Phillips PM2.5×3.0 screw




Color	Quantity	Length	Thread	Head diameter
Black	11	3.0 mm	2.5 mm	5.0 mm




Where used: 2 screws that secure the WLAN module to the system board




Where used: 2 screws that secure the switch cover to the computer



Where used: 2 screws that secure the modem module to the computer




Where used: 4 screws that secure the speaker assembly to the computer




Where used: 1 screw that secures the USB board to the computer

Phillips PM2.0×2.0 broadhead screw




Color	Quantity	Length	Thread	Head diameter
Black	2	2.0 mm	2.0 mm	6.0 mm




Where used: 2 screws that secure the button board to the switch cover


Phillips PM2.0×3.0 broadhead screw



Color	Quantity	Length	Thread	Head diameter
Black	6	3.0 mm	2.0 mm	6.0 mm




Where used: 3 screws that secure the switch cover to the base enclosure




Where used: 3 screws that secure the palm rest to the computer

Phillips PM2.0×4.0 screw




Color	Quantity	Length	Thread	Head diameter
Silver	2	4.0 mm	2.0 mm	4.5 mm




Where used: 2 silver screws that secure the hard drive to the top cover

Phillips PM2.5×9.0 screw




Color	Quantity	Length	Thread	Head diameter
Black	1	9.0 mm	2.5 mm	5.0 mm




Where used: One screw that secures the USB board to the system board


Phillips PM2.5×10.0 captive screw



Color	Quantity	Length	Thread	Head diameter
Silver	6	10.0 mm	2.5 mm	5.0 mm




Where used: 5 captive screws that secure the heat sink to the system board




Where used: One captive screw that secures the hard drive to the computer (screw is secured to the hard drive bracket)

Phillips PM2.5×8.0 captive screw




Color	Quantity	Length	Thread	Head diameter
Black	2	8.0 mm	2.5 mm	5.0 mm




Where used: 2 captive screws that secure the heat sink to the computer


Torx T8M2.5×6.0 screw



Color	Quantity	Length	Thread	Head diameter
Black	25	6.0 mm	2.5 mm	5.0 mm



Where used: 22 screws that secure the top cover to the base enclosure.



Where used: 3 screws that secure the system board to the base enclosure.

8 **Backup and recovery**

Backup and recovery in Windows Vista

Overview

To protect your information, use the Backup and Restore Center to back up individual files and folders, back up your entire hard drive (select models only), or create system restore points. In case of system failure, you can use the backup files to restore the contents of your computer.

The Backup and Restore Center provides the following options:

- Backing up individual files and folders
- Backing up the entire hard drive (select models only)
- Scheduling automatic backups (select models only)
- Creating system restore points
- Recovering individual files
- Restoring the computer to a previous state
- Recovering information using recovery tools

NOTE: For detailed instructions, perform a search for these topics in Help and Support.

NOTE: In case of system instability, HP recommends that you print the recovery procedures and save them for later use.

Backing up your information

Recovery after a system failure is as complete as your most current backup. You should create your initial backup immediately after software setup. As you add new software and data files, you should continue to back up your system on a regular basis to maintain a reasonably current backup.

You can back up your information to an optional external hard drive, a network drive, or discs.

Note the following when backing up:

- Store personal files in the Documents folder, and back it up regularly.
- Back up templates that are stored in their associated programs.
- Save customized settings that appear in a window, toolbar, or menu bar by taking a screen shot of your settings. The screen shot can be a time-saver if you have to reset your preferences.

To create a screen shot:

- 1. Display the screen you want to save.
- 2. Copy the screen image:

To copy only the active window, press alt+fn+prt sc.

To copy the entire screen, press fn+prt sc.

Open a word-processing document, and then select **Edit > Paste**.

The screen image is added to the document.

- 4. Save the document.
- When backing up to discs, use any of the following types of discs (purchased separately): CD-R, CD-RW, DVD+R, DVD+R DL, DVD-R, DVD-R DL, or DVD±RW. The discs you use will depend on the type of optical drive installed in your computer.
- NOTE: DVDs and DVDs with double-layer (DL) support store more information than CDs, so using them for backup reduces the number of recovery discs required.
- When backing up to discs, number each disc before inserting it into the optical drive of the computer.

To create a backup using Backup and Restore Center , follow these steps:

NOTE: Be sure that the computer is connected to AC power before you start the backup process.

NOTE: The backup process may take over an hour, depending on file size and the speed of the computer.

- Select Start > All Programs > Maintenance > Backup and Restore Center.
- Follow the on-screen instructions to back up your entire computer (select models only) or your files.
- NOTE: Windows includes the User Account Control feature to improve the security of your computer. You may be prompted for your permission or password for tasks such as installing software, running utilities, or changing Windows settings. Refer to Help and Support for more information.

Performing a recovery

In case of system failure or instability, the computer provides the following tools to recover your files:

- Windows recovery tools: You can use the Backup and Restore Center to recover information you have previously backed up. You can also use Windows Startup Repair to fix problems that might prevent Windows from starting correctly.
- f11 recovery tools: You can use the f11 recovery tools to recover your original hard drive image. The image includes the Windows operating system and software programs installed at the factory.
- NOTE: If you are unable to boot (start up) your computer, you must purchase a Windows Vista operating system DVD to reboot the computer and repair the operating system. For additional information, refer to the "Using a Windows Vista operating system DVD (purchased separately)" section in this guide.

Using the Windows recovery tools

To recover information you previously backed up, follow these steps:

- Click Start > All Programs > Maintenance > Backup and Restore Center.
- 2. Follow the on-screen instructions to recover your entire computer (select models only) or your files.
- NOTE: Windows includes the User Account Control feature to improve the security of your computer. You may be prompted for your permission or password for tasks such as installing software, running utilities, or changing Windows settings. Refer to Help and Support for more information.

To recover your information using Startup Repair, follow these steps:

- △ CAUTION: Using Startup Repair completely erases hard drive contents and reformats the hard drive. All files you have created and any software installed on the computer are permanently removed. When reformatting is complete, the recovery process restores the operating system, as well as the drivers, software, and utilities from the backup used for recovery.
 - If possible, back up all personal files.
 - If possible, check for the presence of the Windows partition and the HP Recovery partition. To find the partitions, select **Start > Computer**.
 - NOTE: If the Windows partition and the HP Recovery partition have been deleted, you must recover your operating system and programs using the Windows Vista operating system DVD and the Driver Recovery disc (both purchased separately). For additional information, refer to the "Using a Windows Vista operating system DVD (purchased separately)" section in this guide.
 - Restart the computer, and then press f8 before the Windows operating system loads.
 - Select Repair your computer.
 - Follow the on-screen instructions.
- NOTE: For additional information on recovering information using the Windows tools, perform a search for these topics in Help and Support.

Using f11

△ CAUTION: Using f11 completely erases hard drive contents and reformats the hard drive. All files you have created and any software installed on the computer are permanently removed. The f11 recovery tool reinstalls the operating system and HP programs and drivers that were installed at the factory. Software not installed at the factory must be reinstalled.

To recover the original hard drive image using f11, follow these steps:

- If possible, back up all personal files. 1.
- If possible, check for the presence of the HP Recovery partition. To find the partition, select Start > Computer.
- NOTE: If the HP Recovery partition has been deleted, you must recover your operating system and programs using the Windows Vista operating system DVD and the Driver Recovery disc (both purchased separately). For additional information, refer to the "Using a Windows Vista operating system DVD (purchased separately)" section in this guide.

- Turn on or restart the computer, and then press esc while the "Press the ESC key for Startup Menu" message is displayed at the bottom of the screen.
- Press f11 while the "Press <F11> for recovery" message is displayed on the screen.
- 5. Follow the on-screen instructions.

Using a Windows Vista operating system DVD (purchased separately)

If you are unable to boot (start up) your computer, you must purchase a Windows Vista operating system DVD to reboot the computer and repair the operating system. Make sure that your most recent backup (stored on discs or on an external drive) is easily accessible. To order a Windows Vista operating system DVD, go to http://www.hp.com/support, select your country or region, and follow the on-screen instructions. You can also order the DVD by calling technical support. For contact information, refer to the Worldwide Telephone Numbers booklet included with the computer.

△ CAUTION: Using a Windows Vista operating system DVD completely erases hard drive contents and reformats the hard drive. All files you have created and any software installed on the computer are permanently removed. When reformatting is complete, the recovery process helps you restore the operating system, as well as drivers, software, and utilities.

To initiate recovery using a Windows Vista operating system DVD, follow these steps:

- NOTE: This process takes several minutes.
 - 1. If possible, back up all personal files.
 - Restart the computer, and then insert the Windows Vista operating system DVD into the optical drive before the Windows operating system loads.
 - When prompted, press any keyboard key. 3.
 - Follow the on-screen instructions. 4.
 - **5**. Click Next.
 - Select Repair your computer. 6.
 - Follow the on-screen instructions.

Backup and recovery in Windows XP

Overview

To protect your information, use the Windows Backup utility (select models only) to back up files and folders or create recovery points. In case of system failure, you can use the backup files to restore your computer.

Windows provides the following options:

- Backing up individual files and folders
- Backing up all files and folders
- Scheduling automatic backups
- Creating recovery points
- Recovering information
- NOTE: For detailed instructions, perform a search for these topics in Help and Support.

NOTE: In case of system instability, HP recommends that you print the recovery procedures and save them for later use.

Backing up your information

Recovery after a system failure is as complete as your most current backup. You should create your initial backup immediately after software setup. As you add new software and data files, you should continue to back up your system on a regular basis to maintain a reasonably current backup.

You can back up individual files or folders to an optional external hard drive or to a network drive.

Note the following when backing up:

- Store personal files in the My Documents folder, and back it up periodically.
- Back up templates stored in their associated programs.
- Save customized settings that appear in a window, toolbar, or menu bar by taking a screen shot of your settings. The screen shot can be a time saver if you have to reset your preferences.

To copy the screen and paste it into a word-processing document:

- Display the screen you want to save.
- b. Copy the screen image:

To copy only the active window, press alt+fn+prt sc.

To copy the entire screen, press fn+prt sc.

Open a word-processing document, click **Edit > Paste**.

The screen image is added to the document.

Save the document.

To create a backup using the Windows Backup utility, follow these steps:

NOTE: Be sure that the computer is connected to AC power before you start the backup process.

NOTE: The backup process may take over an hour, depending on file size and the speed of the computer.

- Click Start > All Programs > Accessories > System Tools > Backup.
- Follow the on-screen instructions.

Performing a recovery

In case of system failure or instability, the computer provides the following tools to recover your files:

- Windows recovery tools (select models only): You can use the Windows Backup utility to recover information you have previously backed up.
- Operating System and Driver Recovery discs (included with your computer): You can use the discs to recover your operating system and programs installed at the factory.

Recovering your information

To recover information you previously backed up, follow these steps:

- If possible, back up all personal files.
- Click Start > All Programs > Accessories > System Tools > Backup.

The Backup or Restore Wizard opens.

- 3. Click Restore files and settings, and then click Next.
- Follow the on-screen instructions.
- NOTE: For additional information on initiating a recovery in Windows, perform a search for this topic in Help and Support.

Recovering the operating system and programs


△ CAUTION: The recovery process reformats and completely erases the hard drive. All files you have created and any software installed on the computer are permanently removed. The recovery process reinstalls the original operating system, software, and drivers. Software, drivers, and updates not installed by HP must be manually reinstalled.

To recover your operating system and programs, follow these steps:

- 1. If possible, back up all personal files.
- Insert the Operating System disc into the optical drive. 2.
- 3. Shut down the computer.
- 4. Turn on the computer.
- 5. Follow the on-screen instructions to install the operating system.
- After the operating system is installed, remove the Operating System disc and insert the Driver 6. Recovery disc.
- Follow the on-screen instructions to install the drivers and programs.


Connector pin assignments

Audio-in (microphone)




Pin	Signal
1	Audio signal in
2	Audio signal in
3	Ground

Audio-out (headphone)




Pin	Signal
1	Audio out, left channel
2	Audio out, right channel
3	Ground

External monitor




Pin	Signal
1	Red analog
2	Green analog
3	Blue analog
4	Not connected
5	Ground
6	Ground analog
7	Ground analog
8	Ground analog
9	+5 VDC
10	Ground
11	Monitor detect
12	DDC 2B data
13	Horizontal sync
14	Vertical sync
15	DDC 2B clock

HDMI




Pin	Signal
1	Transition minimized differential signal (TDMS) data 2+
2	Transition minimized differential signal (TDMS) data 2 shield
3	Transition minimized differential signal (TDMS) data 2-
4	Transition minimized differential signal (TDMS) data 1+
5	Transition minimized differential signal (TDMS) data 1 shield
6	Transition minimized differential signal (TDMS) data 1 shield
7	Transition minimized differential signal (TDMS) data 0+
8	Transition minimized differential signal (TDMS) data 0 shield
9	Transition minimized differential signal (TDMS) data 0-
10	Transition minimized differential signal (TDMS) Clock +
11	Transition minimized differential signal (TDMS) data clock shield
12	Transition minimized differential signal (TDMS) data clock-
13	Consumer electronics control (CEC)
14	No connect
15	Display data channel (DDC) clock
16	Display data channel (DDC) data
17	Ground
18	+5V Power
19	Hot plug detect

RJ-11 (modem)




Pin	Signal
1	Unused
2	Tip
3	Ring
4	Unused
5	Unused
6	Unused

RJ-45 (network)



Pin	Signal
1	Transmit +
2	Transmit -
3	Receive +
4	Unused
5	Unused
6	Receive -
7	Unused
8	Unused

Universal Serial Bus



Pin	Signal
1	+5 VDC
2	Data -
3	Data +
4	Ground

10 Power cord set requirements

The wide range input feature of the computer permits it to operate from any line voltage from 100 to 120 volts AC or from 220 to 240 volts AC.

The 3-conductor power cord set included with the computer meets the requirements for use in the country or region where the equipment is purchased.

Power cord sets for use in other countries and regions must meet the requirements of the country or region where the computer is used.

Requirements for all countries and regions

The requirements listed below are applicable to all countries and regions:

- The length of the power cord set must be at least 1.5 m (5.0 ft) and no more than 2.0 m (6.5 ft).
- All power cord sets must be approved by an acceptable accredited agency responsible for evaluation in the country or region where the power cord set will be used.
- The power cord sets must have a minimum current capacity of 10 amps and a nominal voltage rating of 125 or 250 V AC, as required by the power system of each country or region.
- The appliance coupler must meet the mechanical configuration of an EN 60 320/IEC 320 Standard Sheet C13 connector for mating with the appliance inlet on the back of the computer.

Requirements for specific countries and regions

Country/region	Accredited agency	Applicable note number
Australia	EANSW	1
Austria	OVE	1
Belgium	CEBC	1
Canada	CSA	2
Denmark	DEMKO	1
Finland	FIMKO	1
France	UTE	1
Germany	VDE	1
Italy	IMQ	1
Japan	METI	3
The Netherlands	KEMA	1
Norway	NEMKO	1
The People's Republic of China	CCC	5
South Korea	EK	4
Sweden	SEMKO	1
Switzerland	SEV	1
Taiwan	BSMI	4
The United Kingdom	BSI	1
The United States	UL	2

- 1. The flexible cord must be Type HO5VV-F, 3-conductor, 1.0-mm² conductor size. Power cord set fittings (appliance coupler and wall plug) must bear the certification mark of the agency responsible for evaluation in the country or region where it will be used.
- 2. The flexible cord must be Type SPT-3 or equivalent, No. 18 AWG, 3-conductor. The wall plug must be a two-pole grounding type with a NEMA 5-15P (15 A, 125 V) or NEMA 6-15P (15 A, 250 V) configuration.
- The appliance coupler, flexible cord, and wall plug must bear a "T" mark and registration number in accordance with the Japanese Dentori Law. The flexible cord must be Type VCT or VCTF, 3-conductor, 1.00-mm² conductor size. The wall plug must be a two-pole grounding type with a Japanese Industrial Standard C8303 (7 A, 125 V) configuration.
- 4. The flexible cord must be Type RVV, 3-conductor, 0.75-mm² conductor size. Power cord set fittings (appliance coupler and wall plug) must bear the certification mark of the agency responsible for evaluation in the country or region where it will be used.
- 5. The flexible cord must be Type VCTF, 3-conductor, 0.75-mm² conductor size. Power cord set fittings (appliance coupler and wall plug) must bear the certification mark of the agency responsible for evaluation in the country or region where it will be used.

11 Recycling

Battery

When a battery has reached the end of its useful life, do not dispose of the battery in general household waste. Follow the local laws and regulations in your area for computer battery disposal.

Display

- ⚠ **WARNING!** The backlight contains mercury. Exercise caution when removing and handling the backlight to avoid damaging this component and causing exposure to the mercury.
- △ CAUTION: The procedures in this chapter can result in damage to display components. The only components intended for recycling purposes are the liquid crystal display (LCD) panel and the backlight. When you remove these components, handle them carefully.
- NOTE: Materials Disposal. This HP product contains mercury in the backlight in the display assembly that might require special handling at end-of-life. Disposal of mercury may be regulated because of environmental considerations. For disposal or recycling information, contact your local authorities, or see the Electronic Industries Alliance (EIA) Web site at http://www.eiae.org.


This section provides disassembly instructions for the display assembly. The display assembly must be disassembled to gain access to the backlight (1) and the liquid crystal display (LCD) panel (2).




NOTE: The procedures provided in this chapter are general disassembly instructions. Specific details, such as screw sizes, quantities, and locations, and component shapes and sizes, can vary from one computer model to another.

Perform the following steps to disassemble the display assembly:

Remove all screw covers (1) and screws (2) that secure the display bezel to the display assembly.




- Lift up and out on the left and right inside edges (1) and the top and bottom inside edges (2) of the display bezel until the bezel disengages from the display assembly.
- Remove the display bezel (3).




Remove all screws (1) that secure the display panel assembly to the display enclosure.


5. Remove the display panel assembly (2) from the display enclosure.



- **6.** Turn the display panel assembly upside down.
- 7. Remove all screws that secure the display panel frame to the display panel.




- 8. Use a sharp-edged tool to cut the tape (1) that secures the sides of the display panel to the display panel frame.
- 9. Remove the display panel frame (2) from the display panel.




10. Remove the screws **(1)** that secure the backlight cover to the display panel.

11. Lift the top edge of the backlight cover (2) and swing it outward.




- 12. Remove the backlight cover.
- 13. Turn the display panel right-side up.
- 14. Remove the backlight cables (1) from the clip (2) in the display panel.




15. Turn the display panel upside down.

⚠ WARNING! The backlight contains mercury. Exercise caution when removing and handling the backlight to avoid damaging this component and causing exposure to the mercury.


16. Remove the backlight frame from the display panel.




17. Remove the backlight from the backlight frame.



- **18.** Disconnect the display panel cable **(1)** from the LCD panel.
- 19. Remove the screws (2) that secure the LCD panel to the display rear panel.
- 20. Release the LCD panel (3) from the display rear panel.
- **21**. Release the tape **(4)** that secures the LCD panel to the display rear panel.



22. Remove the LCD panel.



23. Recycle the LCD panel and backlight.

Index

A	boot options 88	navigating and selecting in
AC adapter, spare part	boot order 88	Linux 90
number 28	bottom components 14	navigating and selecting in
antenna, disconnecting 59	built-in device options 89	Windows 84
audio, product description 3	button components 8	restoring factory settings in
audio-in (microphone) jack	buttons	Linux 91
location 11	Info Center 8	restoring factory settings in
pin assignments 130	power 9	Windows 85
audio-out (headphone) jack	QuickLook 8	Security menu in Linux 91
location 11	TouchPad 7	Security menu in Windows 86
pin assignments 130		System Configuration menu in
	C	Linux 92
В	cables, service considerations 36	System Configuration menu in
backing up, Windows Vista 124	caps lock light 8	Windows 87
backing up, Windows XP 128	chipset, product description 1	using in Linux 90
Backup and Restore	components	using in Windows 84
Center 124, 125	bottom 14	computer specifications 95
base enclosure, spare part	buttons 8	connectors
number 22, 30	display 6	power 12
battery	front 11	service considerations 36
location 14	keys 9	
removal 42	left-side 13	D
spare part number 23, 30, 42	lights 8	device configurations 88
battery bay 14	pointing devices 7	Diagnostics menu
battery connector board, spare	right-side 12	Linux 92
part number 30	speakers 8	Windows 87
battery latches 14	top 6	discs
battery light 12	TouchPad 7	Driver Recovery 129
BIOS administrator password 86	computer feet	Operating System 129
Blu-ray ROM with LightScribe DVD	locations 41	Disk Sanitizer 87
±RW SuperMulti DL Drive	spare part number 41	diskette drive
precautions 36	Computer Setup	precautions 36
removal 48	accessing in Linux 90	product description 3
spare part	accessing in Windows 84	display
number 22, 27, 30, 48	Diagnostics menu in Linux 92	components 6
specifications 99	Diagnostics menu in	illustrated 6
Bluetooth module	Windows 87	display assembly
removal 55	File menu 91	removal 60
spare part	File menu in Windows 86	spare part number 31, 60
number 22, 29, 31, 55		

display bezel	fan	J
removal 62	removal 75	jacks
spare part number 17, 31, 62	spare part number 18, 75	audio-in 11
display cable kit, spare part	feet	audio-out 11
number 31, 64	locations 41	headphone 11
display component recycling 137	spare part number 41	microphone 11
· · · · · · · · · · · · · · · · · · ·	File menu	
display components 6		· · · · · · · · · · · · · · · · · · ·
display enclosure, spare part	Linux 91	network (RJ-45) 13
number 16, 25, 31	Windows 86	17
display hinge	fn key 9	K
removal 63	front components 11	key components 9
spare part number 17, 31, 63	function keys 10	keyboard
display panel, removal 63		product description 4
display specifications 96	G	removal 43
drive light 11	graphics, product description 1	spare part numbers 17, 31, 43
DriveLock password 86	grounding equipment and	keypad keys 10
DriveLock, automatic 87	methods 39	keys
Driver Recovery disc 129		esc 9
drives	н	fn 9
	hard disk test 87	function 10
boot order 88	hard drive	
preventing damage 36		keypad 10
Dual-Core CPU 88	precautions 36	Windows applications 9
DVD-ROM Drive	product description 2	Windows logo 9
spare part number 22, 27, 48	removal 53	
specifications 100	spare part	L
DVD±RW and CD-RW SuperMulti	numbers 22, 27, 31, 32, 33	language, changing in Computer
Double-Layer Combo Drive with	, 34, 53	Setup 87
LightScribe	specifications 97	left-side components 13
spare part	hard drive bracket, removal 54	legacy support, USB 84, 88
number 22, 27, 31, 48	hard drive recovery 126	light components 8
specifications 98	HDMI port	lights
specifications 90	location 13	battery 12
E	pin assignments 132	caps lock 8
	headphone (audio-out) jack	drive 11
electrostatic discharge 37	· · · · · · · · · · · · · · · · · · ·	
esc key 9	location 11	optical drive 12
Ethernet, product description 3	pin assignments 130	power 9
Execution Disable 88	heat sink	wireless 11
ExpressCard assembly, spare part	removal 75	
number 18, 33	spare part number 18, 31, 75	M
ExpressCard slot 13	hinge	mass storage devices, spare part
ExpressCard slot bezel,	removal 63	numbers 27
illustrated 25	spare part number 17, 63	Media Card Reader 11
external monitor port	HP QuickLook 2 88	memory map specifications 104
location 13		memory module
pin assignments 131	T.	product description 2
pin assigninents 101	I/O address specifications 102	removal 46
F	Info Center 8	spare part number 34
		•
f11 recovery 126	internal display switch 6	spare part numbers 46
	interrupt specifications 101	microphone (audio-in) jack
		location 11
		pin assignments 130

microphone, internal 6	modem (RJ-11) jack 133	graphics 1
model name 1	monitor port 131	hard drives 2
modem (RJ-11) jack	network (RJ-45) jack 134	keyboard 4
location 12	RJ-11 133	memory module 2
pin assignments 133	Universal Serial Bus (USB)	modem module 3
modem module	port 134	operating system 4
product description 3	plastic parts 35	optical drives 3
removal 69	Plastics Kit	panels 1
spare part number 18, 30, 69	contents 25	pointing device 4
monitor port	spare part number 25, 31	ports 4
location 13	pointing device	power requirements 4
pin assignments 131	description 4	processors 1
, ,	illustrated 7	product description 4
N	pointing device components	product name 1
network (RJ-45) jack	TouchPad 7	security 4
location 13	TouchPad buttons 7	serviceability 5
.000.00	TouchPad scroll zone 7	wireless 3
0	port options 89	product name 1
Operating System disc 129	ports	product name 1
operating system, product	external monitor 13	Q
description 4	HDMI 13	QuickLook 8
optical disk drive connector board,	monitor 13	QUICKEOOK
spare part number 30		R
optical drive	product description 4	recovery partition 126
bezel 25	Universal Serial Bus	removal/replacement
location 12	(USB) 12, 13	preliminaries 35
	power button 9	•
precautions 36	power button board	procedures 40
product description 3	removal 68	restore security defaults 89
removal 48	spare part number 68	restore the factory settings 86
spare part numbers 22, 27, 48	power connector 12	restoring the hard drive 126
specifications 98, 99, 100	power connector cable,	right-side components 12
optical drive light 12	illustrated 26	RJ-11 (modem) jack
_	power cord	location 12
P	set requirements 135	pin assignments 133
packing guidelines 38	spare part number 29	RJ-11 (modem) jack cable,
palm rest	spare part numbers 28	illustrated 26
removal 51	power light 9	RJ-45 (network) jack
spare part number 31, 51	power requirements, product	location 13
panels, product description 1	description 4	pin assignments 134
passwords 86	processor	removal 77
pin assignments	product description 1	spare part number 77
audio-in (microphone)	removal 79	RJ-45 (network) jack cable,
jack 130	spare part	illustrated 26
audio-out (headphone)	numbers 18, 30, 79	RTC battery
jack 130	product description	removal 73
external monitor port 131	audio 3	spare part number 22, 29, 73
HDMI 132	chipset 1	rubber kit, spare part
headphone (audio-out)	diskette drive 3	number 31, 41
jack 130	Ethernet 3	run-in test 87
microphone (audio-in)	external media cards 3	
jack 130		

\$	System Configuration menu in	T
SATA (Serial Advanced	Linux 92	thermal material, replacement 77
Technology Attachment) devices	System Configuration menu in	tools required 35
AHCI (Advanced Host	Windows 87	top components 6
Controller Interface) 88	speaker kit	top cover
IDE (Integrated Drive	spare part number 31	removal 66
Electronics) 88	speakers	spare part number 18, 31, 66
Screw Kit	location 8	TouchPad 7
contents 105	removal 50	TouchPad buttons 7
spare part number 28, 31	spare part number 18, 50	TouchPad cable, illustrated 26
screw listing 105	specifications	TouchPad scroll zone 7
security cable slot 13	Blu-ray ROM with LightScribe	transporting guidelines 38
Security menu	DVD±RW SuperMulti DL	transporting guidelines 30
Automatic DriveLock 87	Drive 99	U
		Unified Extensible Firmware
change password 86	computer 95	
Disk Sanitizer 87	display 96	Interface (UEFI) mode 88
DriveLock 86	DVD-ROM Drive 100	USB cable, illustrated 26
HP SpareKey 86	DVD±RW and CD-RW	USB connector and cable, spare
HP SpareKey enrollment 86	SuperMulti Double-Layer	part number 22
Linux 91	Combo Drive with	USB connector module,
password policy 86	LightScribe 98	removal 71
set up BIOS Administrator	hard drive 97	USB legacy support 84, 88
password 86	I/O addresses 102	USB port
System IDs 87	interrupts 101	location 13
user management 86	memory map 104	pin assignments 134
Windows 86	optical drive 98, 99, 100	USB port, location 12
security, product description 4	system DMA 100	
service considerations 35	start-up test 87	V
service tag 15, 40	static-shielding materials 39	vents 13
serviceability, product	switch cover	Virtualization Technology 88
description 5	removal 43	
set security level 89	spare part number 17, 30, 43	W
setup utility	switches	webcam module, spare part
Diagnostics menu in Linux 92	internal display 6	number 31
Diagnostics menu in	wireless 11	Windows applications key 9
Windows 87	system board	Windows Backup utility 128, 129
File menu 91	removal 81	Windows logo key 9
File menu in Windows 86	spare part number 18, 33, 81	Windows recovery 125, 129
navigating and selecting in	System Configuration menu	Windows Vista operating system
Linux 90	Linux 92	DVD 127
navigating and selecting in	Windows 87	wireless light 11
Windows 84	system date and time 86	wireless switch 11
restoring factory settings in	System Diagnostics menu 87	wireless, product description 3
Linux 91	system DMA 100	WLAN antennas
restoring factory settings in	system fan 88	disconnecting 59
Windows 85	system IDs 87	location 6
Security menu in Linux 91	system information 86	WLAN module
Security menu in Windows 86	system memory map 104	removal 56
- 122mm, mana m mmaana 90	-yy	spare part numbers 19, 56
		workstation guidelines 38

